## Product Details for 146898



146898

Active

## .4mm, .5mm, .6mm, .8mm, 1mm, Fine Pitch, Surface Mount, Stacking Bd Connectors

5 of 6 RoHS/ELV Compliant (Find RoHS Compliant Alternates/Compliance Statement)

#### **Product Highlights:**

- Family Name = Free Height
- 1.00 mm Centerline
- Number of Positions = 64
- In -Line Contact Layout

View all Features

## **Quick Links**

Check Pricing & Availability Search for Tooling View Mating Products (18) Product Feature Selector Contact Us About This Product

#### **Documentation & Additional Information**

## **Product Drawings:**

PLUG ASSY, W/VACUUM COVER, 1.0mm FH(IEEE 1386) CONNECTO (PDF, English)

## Catalog Pages/Data Sheets:

None Available

#### **Product Specifications:**

? None Available

## **Application Specifications:**

? None Available

#### Instruction Sheets:

? None Available

## CAD Files: (CAD Format & Compression Information

- 2 3D Model (STEP, Version C)
- ? 3D Model (IGES, Version C)
- ? 2D Drawing (DXF, Version C)

# Additional Information:

-to-Bd

Product Line Information

## Additional Product Images:

? Product Photo

#### Related Products:

- ? Tooling
- ? Mating Products (18)

List all Documents

## **Product Features**

(Please use the Product Drawing for all design activity)

#### **Product Type Features:**

- ? Product Type = Plug
- ? Number of Positions
- ? PCB Mount Angle = Vertical
- ? Keved = No
- ? Comment = IEEE 1386 Mezzanine Connector.

- ? Housing Material = LCP

## **Body Related Features:**

- ? Centerline (mm [in]) \_\_ = 1.00 [0.039]
- Board -to Board Stack Height (mm [in]) [0.354], 11.00 [0.433], 14.00 [0.551]
- ? Locating Posts = With
- ? Vacuum Cover = With
- ? Number of Rows = Dual

# Contact Related Features:

- ? Family Name = Free Height
- ? Contact Layout = In -Line
- ? Contact Material = Copper Alloy
- Contact Mating Area Plating = Gold (30)
- ? Contact Termination Area Plating = Tin -Lead over Nickel

## Housing Related Features:

- ? Housing Color = Black
- ? Housing Flammability Rating = UL 94V
- ? Housing Material Temperature = High

## **Industry Standards:**

? RoHS/ELV Compliance = ELV compliant, 5 of 6 Compliant

-0

¿ <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in-Paste capable to 245°C, Pin in-Paste capable to 260°C

## **Packaging Related Features:**

? Packaging Method = Tape & Reel

#### Other:

? Brand = AMP