

## This document was generated on 01/14/2011

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	0546420420		<b></b>	
Status:	0546420439 Planned for Obso	losconco		
Overview:	ieee 1394	lescence	~~~	Z
Description:	0.80mm (.031") Pitch IEEE 1394a-2000 Shielded I/O PCB Socket, Right Angle, Mini Type, Lead-free			0
Documents:				
3D Model		Product Specification PS-54642-014 (PDF)	Joh	D.
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	Vru	Series
General			image - Re	eference only
Product Family		I/O Connectors		
Series		<u>54642</u>	EU RoHS	<u>China RoHS</u>
Application		Wire-to-Board	ELV and RoHS	
Component Type		Receptacle	Compliant	
Overview		<u>ieee_1394</u>	REACH SVHC	
Product Name		IEEE 1394	Not Reviewed	
Туре		N/A	Low-Halogen Status Not Reviewed	
Physical		N1/A	Need more informati	
Boot Color		N/A	environmental comp	bliance?
Circuits (Loaded)		4		
Circuits (maximum)		4	Email productcomplia	
Color - Resin		Black		mber RoHS Certificate of
Gender		Male	Compliance, <u>click her</u>	<u>e</u>
Lock to Mating Part		Yes	Please visit the Conta	at Lip position for any
Material - Metal		Phosphor Bronze	non-product complian	
Material - Plating Mat		Gold, Tin	non-product complian	ce questions.
Material - Plating Ter	mination	Tin		
Material - Resin		High Temperature Thermoplastic		
Number of Rows		2		
Orientation		Right Angle	Search Parts in thi	s Series
PC Tail Length		2.00mm (.079")	<u>54642</u> Series	
PCB Locator		Yes		
PCB Retention		Yes	Mates With	
PCB Thickness - Rec	commended	0.80mm (.031")	IEEE1394 4Pin Plug	g
Packaging Type		Tray		
Panel Mount		No		
Pitch - Mating Interfa		0.80mm (.031")		
Pitch - Termination Ir	nterface	0.80mm (.031")		
Plating min - Mating		0.762µm (30µ")		
Plating min - Termina		0.914µm (36µ"), 3.048µm (120µ")		
Polarized to Mating F	Part	Yes		
Polarized to PCB		Yes		
Ports		1		
Surface Mount Comp		No		
Temperature Range		-25°C to +85°C		
Termination Interface		Through Hole		
Waterproof / Dustpro	of	No		
Wire Size AWG		N/A		
Electrical	Ott	0.54		
Current - Maximum p	Contact	0.5A		
Shield Type		Full Shield		
Shielded		Yes		
Voltage - Maximum		5V AC (RMS)/DC		

Material Info

**Reference - Drawing Numbers** Product Specification

Sales Drawing

PS-54642-014, RPS-54030-038, RPS-54516-001, RPS-54516-026, RPS-54642-017 SD-54642-013

This document was generated on 01/14/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION