# Product Details for 1 -120534 -2



1-120534 -2

✓ Active

# .4mm, .5mm, .6mm, .8mm, 1mm, Fine Pitch, Surface Mount, Stacking Bd -to-Bd Connectors

5 of 6 RoHS/ELV Compliant (Find RoHS Compliant Alternates/Compliance Statement)

#### **Product Highlights:**

- Plua
- Family Name = Free Height
- 2 1.00 mm Centerline
- ? Number of Positions = 84
- ? In -Line Contact Layout

View all Features

# **Quick Links**

Check Pricing &
Availability
Search for Tooling
View Mating
Products (24)
Product Feature
Selector
Contact Us About
This Product

#### **Documentation & Additional Information**

#### **Product Drawings:**

PLUG ASSY, W/COVER (PDF, English)

#### Catalog Pages/Data Sheets:

? None Available

#### **Product Specifications:**

? None Available

#### **Application Specifications:**

? None Available

#### **Instruction Sheets:**

? None Available

#### CAD Files: (CAD Format & Compression Information

- ? 3D Model (STEP, Version H)
- ? 3D Model (IGES, Version H)
- ? 2D Drawing (DXF, Version H)

#### Additional Information:

Product Line Information

# Additional Product Images:

? Product Photo

#### Related Products:

- ? Tooling
- ? Mating Products (24)

List all Documents

# Product Type Features:

**Product Features** 

- ? Product Type = Plug
- ? Number of Positions = 84
- ? PCB Mount Angle = Vertical
- ? Keyed = No
- ? Comment = IEEE 1386 Mezzanine Connector.

# Body Related Features:

- ? Centerline (mm [in]) = 1.00 [0.039]
- Board -to -Board Stack Height (mm [in]) = 10.00 [0.394], 12.00 [0.472], 13.00 [0.512], 15.00 [0.590]

(Please use the Product Drawing for all design activity)

- ? Locating Posts = Without
- ? Vacuum Cover = With
- ? Number of Rows = Dual

#### **Contact Related Features:**

- ? Family Name = Free Height
- ? Contact Layout = In -Line
- ? Contact Material = Copper Alloy
- ? Contact Mating Area Plating = Gold (50)
- Contact Termination Area Plating = Tin -Lead over Nickel

### **Housing Related Features:**

- ? Housing Color = Black
- ? Housing Material = LCP
- ? Housing Flammability Rating = UL 94V -0
- ? Housing Material Temperature = High

## **Industry Standards:**

- ? RoHS/ELV Compliance = ELV compliant, 5 of 6 Compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in-Paste capable to 245°C, Pin in-Paste capable to 260°C

# **Packaging Related Features:**

? Packaging Method = Tape & Reel

#### Other:

? Brand = AMP