| tyco | | Search By | r In Part Number | n Text | Tip |
|--|--|---|---|---|--------------------------|
| Electronics | | · · · · · · · · · · · · · · · · · · · | omplete or partial part nu | | Go |
| Products Documentation | Resources My Account Custome | r Support About Us | | | |
| tome > Products > By Type > Para | allel (Stacking) Configuration > Product Fe | ature Selector > Produc | ct Details | | |
| Product Details for 1 | - 146893 - 1 | | | | |
| | 7 | | | | |
| and the second se | .4mm, .5mm, .6mm, .8mm | | | -Quick Links | |
| - management | Pitch, Surface Mount, Sta Connectors | аскілд ва | -to-Bd | Check Pricing | & |
| THEFT. MULTING | | | | Availability Search for To | olina |
| C. mmmm | 5 of 6 RoHS/ELV Compliant Alternates/Compliance Statement | | int | View Mating | |
| | Alternates/Compliance Statement, | · | | Products (18) | |
| 1-146893 -1 | Product Highlights: | | | Product Featu Selector | <u>re</u> |
| | ? Receptacle | | | Contact Us At | |
| Active | ? Family Name = Free Height | nt | | This Product | - |
| - ////// | 1.00 mm Centerline Number of Positions = 64 | | | | |
| | In - Line Contact Layout | | | | |
| | View all Features | | | | |
| | | | | | |
| D | | | | | |
| Documentation & Addition | nal Information | | | | |
| Product Drawings: | | | Additional I | | |
| ? <u>RECEPTACLE ASSY</u> (PDF, English) | Y, W/ VACUUM COVER, 1.0mm F | -H(IEEE 1386 | _ ? Produc | ct Line Information | |
| (i bi , English) | | | Additional F | Product Images: | |
| Catalog Pages/Data Shee | ts: | | | ct Photo | |
| ? None Available | | | | | |
| | | | Related Pro | | |
| Product Specifications: | | | ? <u>Toolin</u> | <u>g_</u> | |
| None Available | | | N d = time = | Des durate (40) | |
| None Available | | | ? Mating | <u> Products (18)</u> | |
| Application Specification ? None Available | S: | | ? Mating | <u>3 Products (18)</u> | |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model_ (STEP, V 3D Model_ (IGES, Ve | & Compression Information |) | ? <u>Mating</u> | <u>1 Products (18)</u> | |
| Application Specifications ⁷ None Available Instruction Sheets: ⁷ None Available CAD Files: (CAD Formation ⁷ 3D Model (STEP, V | & Compression Information ersion J) version J) |) .ist all Documents | ? <u>Mating</u> | <u>j Products (18)</u> | |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model (STEP, V 3D Model (IGES, Ve 2D Drawing (DXF, V | & Compression Information ersion J) version J) | | ? <u>Mating</u> | <u>pProducts (18)</u> | |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model_(STEP, V 3D Model_(IGES, Ve 2D Drawing_(DXF, V Product Features (Please | & Compression Information ersion J) version J) Version J) | ist all Documents | | <u>pProducts (18)</u> | |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model (STEP, V 3D Model (IGES, Ve 2D Drawing (DXF, V | & Compression Information () ersion J) Version J) Version J) | | d Features: | <u>pProducts (18)</u> | |
| Application Specifications 7 None Available Instruction Sheets: 7 None Available CAD Files: (CAD Format. 7 3D Model (STEP, V 7 3D Model (IGES, Ve 7 2D Drawing (DXF, V Product Features (Please Product Type Features: 7 Product Type = Rec 7 Number of Positions | & Compression Information ersion J) version J) version J) use the Product Drawing for all design activity) exeptacle = 64 | List all Documents Housing Relate ? Housing C ? Housing M | d Features: Color = Black Material = High T | | |
| Application Specifications 7 None Available Instruction Sheets: 7 None Available CAD Files: (CAD Format. 7 3D Model_ (STEP, V 7 3D Model_ (IGES, Ve 7 2D Drawing_ (DXF, V 7 2D D | & Compression Information ersion J) version J) version J) use the Product Drawing for all design activity) exeptacle = 64 | List all Documents Housing Relate ? Housing C ? Housing M Thermopla | d Features: Color = Black Material = High T astic | Temperature | |
| Application Specifications 7 None Available Instruction Sheets: 7 None Available CAD Files: (CAD Format. 7 3D Model_(STEP, V 7 3D Model_(IGES, Ve 7 2D Drawing_(DXF, V 7 2D Drawing_(DXF, V 7 7 2D Drawing_(DXF, V 7 7 2D Drawing_) Product Type Features: 7 Product Features: 7 Product Type Features: 7 Product Type Features: 7 Product Features: | & Compression Information () ersion J) /ersion J) /ersion J) use the Product Drawing for all design activity) ceptacle = 64 /ertical | List all Documents Housing Relate ? Housing C ? Housing M Thermopla ? Housing F | d Features: Color = Black Material = High T astic | Γemperature ting = UL 94V | -0 |
| Application Specifications 7 None Available Instruction Sheets: 7 None Available CAD Files: (CAD Format. 7 3D Model_(STEP, V 7 3D Model_(IGES, Ve 7 2D Drawing_(DXF, V 7 2D Drawing_(DXF, V 7 7 2D Drawing_(DXF, V 7 7 2D Drawing_) Product Type Features: 7 Product Features: 7 Product Type Features: 7 Product Type Features: 7 Product Features: | & Compression Information ersion J) version J) version J) use the Product Drawing for all design activity) exeptacle = 64 | List all Documents Housing Relate ? Housing C ? Housing M Thermopla ? Housing F | d Features: Color = Black Material = High T astic | Γemperature ting = UL 94V | -0 |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model_(STEP, V 3D Model_(IGES, Ve 2D Drawing_(DXF, V Product Features Product Type Features: Product Type Features: Product Type _= Rec Number of Positions PCB Mount Angle = N Keyed = No Comment = IEEE 138 | & Compression Information () ersion J) /ersion J) /ersion J) use the Product Drawing for all design activity) ceptacle = 64 /ertical | Housing Relate Housing C Housing C Housing M Thermopla Housing F Housing M | d Features: Color = Black Material = High T astic Material Temper | Γemperature ting = UL 94V | -0 |
| Application Specifications 7 None Available Instruction Sheets: 7 None Available CAD Files: (CAD Format. 7 3D Model_(STEP, V 7 3D Model_(IGES, Ve 7 2D Drawing_(DXF, V 7 2D Drawing_(DXF, V 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 | & Compression Information ersion J) ersion J) /ersion J) use the Product Drawing for all design activity) = 64 /ertical 36 Mezzanine Connector. | ist all Documents Housing Relate ? Housing C ? Housing M Thermople ? Housing F ? Housing M Industry Standa ? RoHS/EL | d Features: color = Black laterial = High T astic lammability Rat laterial Temper ards: / Compliance | Γemperature ting = UL 94V | |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model. (STEP, V 3D Model. (IGES, Ve 2D Drawing. (DXF, V Product Features (Please Product Type Features: Product Type Features: PCB Mount Angle = N Keyed. = No Comment = IEEE 138 Body Related Features: Centerline (mm [in]). Board -to - Board Sta | & Compression Information ersion J) ersion J) /ersion J) use the Product Drawing for all design activity) ceptacle = 64 //ertical 36 Mezzanine Connector. = 1.00 [0.039] = 8.00 | ist all Documents Housing Relate P Housing C Housing M Thermopla Housing F Housing M Housing M Industry Standa RoHS/ELV Compliant | d Features: color = Black Material = High T astic lammability Rat Material Temper ards: / Compliance | Femperature ting = UL 94V ature = High . = ELV compliant, 5 | of 6 |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model. (STEP, V 3D Model. (IGES, Ve 2D Drawing. (DXF, V Product Features (Please Product Type Features: Product Type Features: PCB Mount Angle = N Keyed. = No Comment = IEEE 138 Body Related Features: Centerline (mm [in]). Board -to - Board Sta [0.315], 9.00 [0.354], | & Compression Information ersion J) ersion J) /ersion J) use the Product Drawing for all design activity) ceptacle = 64 //ertical 36 Mezzanine Connector. = 1.00 [0.039] ck Height (mm [in]) = 8.00 10.00 [0.394] | List all Documents Housing Relate ? Housing C ? Housing M Thermopla ? Housing F ? Housing M Industry Standa ? RoHS/EL Compliant ? Lead Free | d Features: Color = Black Material = High T astic Nammability Rat Material Temper ards: / Compliance | Temperature ting = UL 94V ature = High . = ELV compliant, 5 ses = Wave sold | of 6 er |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model. (STEP, V 3D Model. (IGES, Ve 2D Drawing(DXF, V 2D Drawing(DXF, V Product Features (Please Product Type Features: Product Type = Rec Number of Positions PCB Mount Angle = N Keyed = No Comment = IEEE 138 Body Related Features: Centerline (mm [in]). Board -to -Board Sta [0.315], 9.00 [0.354], Locating Posts = W | & Compression Information ersion J) ersion J) /ersion J) use the Product Drawing for all design activity) peptacle = 64 //ertical 36 Mezzanine Connector. = 1.00 [0.039] ck Height (mm [in]) = 8.00 10.00 [0.394] | List all Documents Housing Relate P Housing C Housing M Thermopla Housing F Housing M Industry Standa RoHS/ELV Compliant Lead Free capable to | d Features: Color = Black Material = High T astic l'ammability Rat Material Temper ards: / Compliance Solder Process 9 240°C, Wave s | Femperature ting = UL 94V ature = High . = ELV compliant, 5 | of 6 er |
| Application Specifications 7 None Available Instruction Sheets: 7 None Available CAD Files: (CAD Format. 7 3D Model. (STEP, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 2D Drawing. (DXF, V 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, Ve 7 2D Drawing. (D | & Compression Information ersion J) ersion J) /ersion J) use the Product Drawing for all design activity) exeptacle = 64 //ertical 36 Mezzanine Connector. = 1.00 [0.039] ck Height (mm [in]) = 8.00 10.00 [0.394] //ith ith | List all Documents Housing Relate P Housing C Housing M Thermopla Housing F Housing F Housing K Industry Standa RoHS/EL Compliant Lead Free capable to C, Wave s solder cap | d Features: Color = Black Material = High T astic lammability Rati Material Temper ards: / Compliance Solder Process o 240°C, Wave s o older capable to bable to 245°C, | Femperature ting = UL 94V ature = High = ELV compliant, 5 ses = Wave sold solder capable to 26 o 265°C, Reflow Reflow solder capa | of 6 er 60° ble |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model. (STEP, V 3D Model. (IGES, Ve 2D Drawing(DXF, V 2D Drawing(DXF, V Product Features (Please Product Type Features: Product Type = Rec Number of Positions PCB Mount Angle = N Keyed = No Comment = IEEE 138 Body Related Features: Centerline (mm [in]). Board -to -Board Sta [0.315], 9.00 [0.354], Locating Posts = W | & Compression Information ersion J) ersion J) /ersion J) use the Product Drawing for all design activity) exeptacle = 64 //ertical 36 Mezzanine Connector. = 1.00 [0.039] ck Height (mm [in]) = 8.00 10.00 [0.394] //ith ith | ist all Documents Housing Relate Phousing C Housing C Housing M Thermopla Housing F Housing F Housing M Industry Standa RoHS/ELV Compliant Lead Free capable to C, Wave s solder cap to 260°C, | d Features: color = Black Material = High T astic lammability Rat Material Temper ards: / Compliance / Compliance 240°C, Wave s solder capable to able to 245°C, Pin - in - Paste | Temperature ting = UL 94V ature = High . = ELV compliant, 5 ses = Wave sold solder capable to 26 o 265°C, Reflow Reflow solder capa capable to 245°C, | of 6 er 60° ble |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model. (STEP, V 3D Model. (IGES, Ve 2D Drawing. (DXF, V Product Features (Please Product Type Features: Product Type Features: Product Type Features: PCB Mount Angle = No Comment = IEEE 138 Body Related Features: Centerline (mm [in]). Board -to - Board State [0.315], 9.00 [0.354], Locating Posts = W Number of Rows = D | & Compression Information | ist all Documents Housing Relate Phousing C Housing C Housing M Thermopla Housing F Housing F Housing M Industry Standa RoHS/ELV Compliant Lead Free capable to C, Wave s solder cap to 260°C, | d Features: Color = Black Material = High T astic lammability Rati Material Temper ards: / Compliance Solder Process o 240°C, Wave s o older capable to bable to 245°C, | Temperature ting = UL 94V ature = High . = ELV compliant, 5 ses = Wave sold solder capable to 26 o 265°C, Reflow Reflow solder capa capable to 245°C, | of 6 er 60° ble |
| Application Specifications 7 None Available Instruction Sheets: 7 None Available CAD Files: (CAD Format. 7 3D Model. (STEP, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 2D Drawing. (DXF, V 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, V 7 3D Model. (IGES, Ve 7 2D Drawing. (DXF, Ve 7 2D Drawing. (D | & Compression Information ersion J) prsion J) /ersion J) use the Product Drawing for all design activity) peptacle = 64 /ertical 36 Mezzanine Connector. = 1.00 [0.039] ck Height (mm [in]) = 8.00 10.00 [0.394] //ith ith ual : | ist all Documents Housing Relate Phousing C Housing C Housing K Housing F Housing F Housing K Industry Standa RoHS/ELV Compliante Lead Free capable to C, Wave s solder cap to 260°C, l in - Paste c | d Features: Color = Black Material = High T astic Tammability Rat Material Temper ards: / Compliance 240°C, Wave s solder capable to able to 245°C, Pin - in - Paste capable to 260°f | Temperature ting = UL 94V ature = High . = ELV compliant, 5 ses = Wave sold solder capable to 26 o 265°C, Reflow Reflow solder capa capable to 245°C, | of 6 er 60° ble |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model. (STEP, V 3D Model. (IGES, Ve 2D Drawing. (DXF, V Product Features (Please Product Type Features: Product Type Features: PCB Mount Angle = N Keyed = No Comment = IEEE 138 Body Related Features: Centerline (mm [in]). Board -to - Board Stal, Locating Posts = W Vacuum Cover. = W Number of Rows = D Contact Related Features: Family Name = Free Contact Layout. = In | & Compression Information ersion J) ersion J) /ersion J) use the Product Drawing for all design activity) exeptacle = 64 /ertical 36 Mezzanine Connector. = 1.00 [0.039] ck Height (mm [in]) = 8.00 10.00 [0.394] /ith ith ual : Height n -Line | ist all Documents Housing Relate P Housing C Housing M Thermopla Housing F Housing F Housing K Industry Standa RoHS/ELV Compliant Lead Free capable to C, Wave s solder cap to 260°C, in - Paste c | d Features: Color = Black Material = High T astic Tammability Rat Material Temper ards: / Compliance 240°C, Wave s solder capable to able to 245°C, Pin - in - Paste capable to 260°f | Temperature ting = UL 94V ature = High . = ELV compliant, 5 solder capable to 26 o 265°C, Reflow Reflow solder capa capable to 245°C, C | of 6 er 60° ble |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model. (STEP, V 3D Model. (IGES, Ve 2D Drawing. (DXF, V Product Features (Please Product Type Features: Product Type Features: Product Type Features: Product Type Features: Product Type Features: PCB Mount Angle = V Keyed = No Comment = IEEE 138 Body Related Features: Centerline (mm [in]) Board -to - Board Sta [0.315], 9.00 [0.354], Locating Posts = W Vacuum Cover = W Number of Rows = D Contact Related Features: Contact Related Features: Contact Layout = In Contact Material = Co | & Compression Information ersion J) sersion J) /ersion J) use the Product Drawing for all design activity) exeptacle = 64 /ertical 36 Mezzanine Connector. = 1.00 [0.039] ck Height (mm [in]) = 8.00 10.00 [0.394] /ith ith ual : Height n - Line poper Alloy | ist all Documents Housing Relate P Housing C Housing M Thermopla Housing F Housing F Housing K Industry Standa RoHS/ELV Compliant Lead Free capable to C, Wave s solder cap to 260°C, in - Paste c | d Features: olor = Black Material = High T astic Material Temper ards: / Compliance / Compliance / Compliance solder capable to 245°C, Pin - in - Paste capable to 260° mable to 260° | Temperature ting = UL 94V ature = High . = ELV compliant, 5 solder capable to 26 o 265°C, Reflow Reflow solder capa capable to 245°C, C | of 6 er 60° ble |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model. (STEP, V 3D Model. (IGES, Ve 2D Drawing. (DXF, V Product Features (Please Product Type Features: Product Type Features: PCB Mount Angle = N Keyed = No Comment = IEEE 138 Body Related Features: Centerline (mm [in]). Board -to - Board Stat [0.315], 9.00 [0.354], Locating Posts = W Vacuum Cover. = W Number of Rows = D Contact Related Features Family Name = Free Contact Material = Co Contact Material = Co Contact Mating Area | & Compression Information ersion J) ersion J) /ersion J) /use the Product Drawing for all design activity) exeptacle = 64 /ertical 36 Mezzanine Connector. = 1.00 [0.039] ck Height (mm [in]) = 8.00 10.00 [0.394] /ith ith ual : Height n - Line poper Alloy Plating = Gold (50) | ist all Documents Housing Relate P Housing C Housing M Thermopla Housing F Housing F Housing K Industry Standa RoHS/ELX Compliant Lead Free capable to C, Wave s solder cap to 260°C, 1 in - Paste c Packaging Rela Packaging Other: | d Features: color = Black laterial = High T astic lammability Rat laterial Temper ards: / Compliance 240°C, Wave s colder capable to 240°C, Wave s colder capa | Temperature ting = UL 94V ature = High . = ELV compliant, 5 solder capable to 26 o 265°C, Reflow Reflow solder capa capable to 245°C, C | of 6 er 60° ble |
| Application Specifications None Available Instruction Sheets: None Available CAD Files: (CAD Format. 3D Model. (STEP, V 3D Model. (IGES, Ve 2D Drawing. (DXF, V Product Features (Please Product Type Features: Product Type Features: Product Type Features: Product Type Features: Product Type Features: PCB Mount Angle = V Keyed = No Comment = IEEE 138 Body Related Features: Centerline (mm [in]) Board -to - Board Sta [0.315], 9.00 [0.354], Locating Posts = W Vacuum Cover = W Number of Rows = D Contact Related Features: Contact Related Features: Contact Layout = In Contact Material = Co | & Compression Information ersion J) ersion J) /ersion J) /use the Product Drawing for all design activity) exeptacle = 64 /ertical 36 Mezzanine Connector. = 1.00 [0.039] ck Height (mm [in]) = 8.00 10.00 [0.394] /ith ith ual : Height n - Line poper Alloy Plating = Gold (50) | ist all Documents Housing Relate P Housing C Housing M Thermopla Housing F Housing F Housing M Industry Standa RoHS/ELV Compliant Lead Free capable to C, Wave s solder cap to 260°C, in - Paste c Packaging Rela Packaging | d Features: color = Black laterial = High T astic lammability Rat laterial Temper ards: / Compliance 240°C, Wave s colder capable to 240°C, Wave s colder capa | Temperature ting = UL 94V ature = High . = ELV compliant, 5 solder capable to 26 o 265°C, Reflow Reflow solder capa capable to 245°C, C | of 6 er 60° ble |

 Languages
 : English
 Deutsch
 Español
 Português (do Brasil)
 2222222
 Italiano
 2222 (22)
 22 (22)
 222

 Country Sites
 : China
 Japan