

# 0.8 [.031] Printed Circuit Board and Cable Connectors

No Image Available RoHS Compliant (Statement of Compliance)

## **Product Highlights:** 6364973

- Mating Type = Receptacle
- Number of Positions = 68
  Terminate To Printed Circuit Board
- PCB Mount Style = Thru Hole
- Right Angle Mount Angle

View all Features

### **Quick Links**

Additional Information:

Related Products:

? Tooling

Product Line Information

Check Pricing & Availability Search for Tooling Product Feature Selector Contact Us About This Product

## **Documentation & Additional Information**

#### **Product Drawings:**

RECEPTACLE ASSEMBLY, 68 POSITION, SHIELDED, RIGHT AN (PDF, English)

### Catalog Pages/Data Sheets:

? None Available

Active

### **Product Specifications:**

Connector, 0.8mm CHAMP (PDF, English)

## Application Specifications:

CHAMP 0.8mm Cable & Printed Circuit (PC) Board Conne... (PDF,

### Instruction Sheets:

- ? Tooling Kit (PDF, English)
- Mass Termination Tooling Assembly 543580 -1 & Cutter ...
- Manual Arbor Frame Assembly 91085 -2 (PDF, English)

### **CAD Files:**

? None Available

List all Documents

#### Product Features (Please use the Product Drawing for all design activity)

## **Product Type Features:**

- ? Mating Type = Receptacle
- ? Number of Positions = 68
- ? PCB Mount Style = Thru Hole
- ? Mount Angle = Right Angle
- ? SMT Compatible = No
- ? Profile = High
- ? Stacked = No
- ? PCB Polarization = Without
- 2 Special PCB Retention = With
- ? Product Type = Connector
- ? Shell Material = Carbon Steel
- Shielded = Yes
- ? Mating Connector Lock = With
- ? Mating Connector Lock Type = Screwlocks
- Mating Connector Lock Type Material = Stainless Steel

### Termination Related Features:

? Termination Post Length (mm [in]) = 3.56 [0.140]

## **Body Related Features:**

- Center Ground Plate = Without
- ? Number of Rows = 2
- ? Insert Material = Thermoplastic
- ? Insert Flammability Rating = UL 94V -0
- ? Shell Plating = Nickel over Copper

## **Contact Related Features:**

- Contact Mating Area Plating = Gold (30) over Palladium Nickel
- Contact Centerline Spacing (mm [in]) = 0.80 [0.031]
- ? Contact Material = Phosphor Bronze
- ? Contact Termination Area Plating = Tin

## **Housing Related Features:**

- ? Housing Flammability Rating = UL 94V -0
- ? Housing Material = Thermoplastic
- ? Housing Color = Black

## **Industry Standards:**

- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Reflow solder capable to 245°C, Reflow solder capable to
- RoHS/ELV Compliance History = Always was RoHS compliant

### Conditions for Usage:

? Terminate To = Printed Circuit Board

### Other:

Brand = AMP