#### Product Details for 1 -120521 -1



1-120521 -1

✓ Active

# .4mm, .5mm, .6mm, .8mm, 1mm, Fine Pitch, Surface Mount, Stacking Bd Connectors

5 of 6 RoHS/ELV Compliant (Find RoHS Compliant Alternates/Compliance Statement)

### **Product Highlights:**

- ? Receptacle
- ? Family Name = Free Height
- 2 1.00 mm Centerline
- ? Number of Positions = 64
- ? In -Line Contact Layout

View all Features

#### **Quick Links**

Check Pricing &
Availability
Search for Tooling
View Mating
Products (18)
Product Feature
Selector
Contact Us About
This Product

#### **Documentation & Additional Information**

#### **Product Drawings:**

? RECEPTACLE ASSY, 1.0mm FH(IEEE1386) CONNECTOR (PDF, English)

# Catalog Pages/Data Sheets:

None Available

# **Product Specifications:**

? None Available

#### **Application Specifications:**

? None Available

# **Instruction Sheets:**

? None Available

## CAD Files: (CAD Format & Compression Information

- ? 3D Model (STEP, Version H)
- ? <u>3D Model</u> (IGES, Version H)
- ? 2D Drawing (DXF, Version H)

List all Documents

#### Additional Information:

Product Line Information

# Additional Product Images:

? Product Photo

#### Related Products:

-to-Bd

- ? Tooling
- ? Mating Products (18)

Product Features (Please use the Product Drawing for all design activity)

#### **Product Type Features:**

- ? Product Type = Receptacle
- ? Number of Positions = 64
- ? PCB Mount Angle = Vertical
- ? Keyed = No
- ? Comment = IEEE 1386 Mezzanine Connector.

## **Body Related Features:**

- ? Centerline (mm [in]) = 1.00 [0.039]
- Board -to Board Stack Height (mm [in]) = 8.00 [0.315], 9.00 [0.354], 10.00 [0.394]
- ? Locating Posts = With
- ? Vacuum Cover = Without
- ? Number of Rows = Dual

#### **Contact Related Features:**

- ? Family Name = Free Height
- ? Contact Layout = In -Line
- ? Contact Material = Copper Alloy
- ? Contact Mating Area Plating = Gold (50)
- Contact Termination Area Plating = Tin -Lead over Nickel

# Housing Related Features:

- ? Housing Color = Black
- ? Housing Material = High Temperature Thermoplastic
- ? Housing Flammability Rating = UL 94V -0
- ? Housing Material Temperature = High

# Industry Standards:

- RoHS/ELV Compliance = ELV compliant, 5 of 6 Compliant
- Page 12 Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in-Paste capable to 245°C, Pin in-Paste capable to 260°C

#### **Packaging Related Features:**

? Packaging Method = Tape & Reel

#### Other:

? Brand = AMP

Languages : English | Deutsch | Español | Português (do Brasil) | ???????? | Italiano | ???? (?? ) | ?? (? ? ) | ??? | Country Sites : China | Japan