
Product Details for 1 -120528 -1



1-120528 -1

✓ Active

.4mm, .5mm, .6mm, .8mm, 1mm, Fine Pitch, Surface Mount, Stacking Bd Connectors

5 of 6 RoHS/ELV Compliant (Find RoHS Compliant Alternates/Compliance Statement)

Product Highlights:

- ? Receptacle
- Family Name = Free Height
- 2 1.00 mm Centerline
- ? Number of Positions = 64
- ? In -Line Contact Layout

View all Features

Quick Links

Check Pricing &
Availability
Search for Tooling
View Mating
Products (18)
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

? RCPT ASSY,W/COVER,1.0mmFH(IEEE1386) CONNECTOR (PDF, English)

Catalog Pages/Data Sheets:

None Available

Product Specifications:

? None Available

Application Specifications:

? None Available

Instruction Sheets:

? None Available

CAD Files: (CAD Format & Compression Information

- ? 3D Model (STEP, Version J)
- ? 3D Model (IGES, Version J)
- ? 2D Drawing (DXF, Version J)

List all Documents

Additional Information:

Product Line Information

Additional Product Images:

? Product Photo

Related Products:

? Tooling

-to-Bd

? Mating Products (18)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Receptacle
- ? Number of Positions = 64
- ? PCB Mount Angle = Vertical
- ? Keyed = No
- ? Comment = IEEE 1386 Mezzanine Connector.

Body Related Features:

- ? Centerline (mm [in]) = 1.00 [0.039]
- Board -to -Board Stack Height (mm [in]) = 8.00 [0.315], 9.00 [0.354], 10.00 [0.394]
- ? Locating Posts = Without
- ? Vacuum Cover = With
- ? Number of Rows = Dual

Contact Related Features:

- ? Family Name = Free Height
- ? Contact Layout = In -Line
- ? Contact Material = Copper Alloy
- ? Contact Mating Area Plating = Gold (50)
- Contact Termination Area Plating = Tin -Lead over Nickel

Housing Related Features:

- ? Housing Color = Black
- ? Housing Material = High Temperature Thermoplastic
- ? Housing Flammability Rating = UL 94V -0
- ? Housing Material Temperature = High

Industry Standards:

- RoHS/ELV Compliance = ELV compliant, 5 of 6 Compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in-Paste capable to 245°C, Pin in-Paste capable to 260°C

Packaging Related Features:

? Packaging Method = Tape & Reel

Other:

? Brand = AMP

 Languages
 : English |
 Deutsch |
 Español |
 Português (do Brasil) |
 ??????? |
 Italiano |
 ???? (??) |
 ?? (? ?) |
 ???

 Country Sites
 : China |
 Japan |