

Wire to Board Connectors Dynamic Series Connectors / D-5200 Series D-5 Contact

■Crimp Type Contacts



Receptacle Contact (Used in Receptacle Housing)



Tab Contact (Used in Tab Housing)

Gold Plating Type

Wire Range		Ins. Dia Range	Wire Range Mark	Contact Part Numbers			Application Tooling	
				Receptacle	Tab	Sequetial Tab	Mini-Applicator	Hand Tool
	1.25	<u>mm</u>		ST. 179955-	917802-	84696-1	1366659-2	
16 14	2.20	3~3.8	S	LP. 316040-□	917804-		· ·	234170-1
-\ 4	$-\frac{2.20}{3.50}$			ST. 179956-	917803-	84695-1	1366660-2	234171-1
10	5.50	4~5.2	М		917805-			

 ${f Note}$: Enter the following plating code in Part Number suffix- \Box

- -2: 0.38µm thick gold plating
- -3: 0.76µm thick gold plating
- requirments by multiplying the quantity set for each.
- Minimum order quantity for tooling is one.
- Mini-Applicator is for use on Automachine. (See the preceding page. Contact our Sales Department for details.)
- •Minimum order quantity is provided for each product. When ordering, specify your •Strip Form contacts are used with Mini-Applicator and Loose-Piece contacts are with hand tools.

D-5 α Series Silver Plating Type

Wire Range		Ins. Dia Range	Wire -	Contact Part Numbers	Application Tooling	
				Receptacle	Mini-Applicator	Hand Too
AWG	m m	mm	Range Mark			
20	0.50	1.8~3.23	SS -	ST. 1318985-6	1366757-2	
16	1.25			LP. 1318986-6		91596-1
				ST. 179955-6	1366659-2	
16	1.25	3~3.80	S -	LP. 316040-6		234170-1
14	2.20			=_ == == == ==	1366660-2	
12	3.50	4~ 5.2	М -	ST. 179956-6		234171-1
10	5.50			LP. 316041-6		234171-1
		4.9~7.8		ST. 1318696-6	1366658-4	
8	8 8.00					1366044-

- Minimum order quantity is provided for each product. When ordering, specify your requirments by multiplying the quantity set for each.
- Minimum order quantity for tooling is one.
- Note: The contacts part numbered with "-6" are silver plated with 2.54 μm thickness. •Mini-Applicator is for use on Automachine. (See the preceding page. Contact our

Sales Department for details.)

 Strip Form contacts are used with Mini-Applicator and Loose-Piece contacts are with hand tools.