

## **Wire to Board Connectors Dynamic Series Connectors / D-5200 Series D-5 Contact**

## **■**Crimp Type Contacts



Receptacle Contact (Used in Receptacle Housing)



**Tab Contact** (Used in Tab Housing)

## **Gold Plating Type**

Wire Range		Ins. Dia Range	Wire Range Mark	Contact Part Numbers			Application Tooling	
				Receptacle	Tab	Sequetial Tab	Mini-Applicator	Hand Tool
	1.25	<u>mm</u>		ST. 179955-	917802-	84696-1	1366659-2	
16 14	2.20	3~3.8	S	LP. 316040-□	917804-			234170-
_\ <u>4</u>	$-\frac{2.20}{3.50}$			ST. <b>179956-</b>	917803-	84695-1	1366660-2	234171-1
10	5.50	4~5.2	М		917805-			

 ${f Note}$  : Enter the following plating code in Part Number suffix- $\Box$ 

- -2: 0.38µm thick gold plating
- -3: 0.76µm thick gold plating
- requirments by multiplying the quantity set for each.
- Minimum order quantity for tooling is one.
- Mini-Applicator is for use on Automachine. (See the preceding page. Contact our Sales Department for details.)
- •Minimum order quantity is provided for each product. When ordering, specify your •Strip Form contacts are used with Mini-Applicator and Loose-Piece contacts are with hand tools.

## D-5 α Series Silver Plating Type

Wire Range		Ins. Dia Range	Wire -	Contact Part Numbers	Application Tooling	
				Receptacle	Mini-Applicator	Hand Tool
AWG	<b>m</b> m	mm	Range Mark	Neceptable		
20	0.50	1.8~3.23	SS -	ST. <b>1318985-6</b>	1366757-2	
16	1.25			LP. 1318986-6		91596-1
				ST. <b>179955-6</b>	1366659-2	
16	1.25	3~3.80	S -	LP. 316040-6		234170-1
14	2.20			=_ == == == ==	1366660-2	
12	3.50	<b>4~</b> 5.2	М -	ST. 179956-6		234171-1
10	5.50			LP. <b>316041-6</b>		234171-1
		4.9~7.8		ST. 1318696-6	1366658-4	
8	8 8.00					1366044-

- Minimum order quantity is provided for each product. When ordering, specify your requirments by multiplying the quantity set for each.
- Minimum order quantity for tooling is one.
- Note: The contacts part numbered with "-6" are silver plated with 2.54 μm thickness. •Mini-Applicator is for use on Automachine. (See the preceding page. Contact our

Sales Department for details.)

 Strip Form contacts are used with Mini-Applicator and Loose-Piece contacts are with hand tools.