








# Econoseal J Series Connectors <Mark II (+)>

## Contact

Contact	Wire Range	Wire Ins. Diameter	Material/Finish	Part No.		Hand Tool No. (Instruction Sheet)	
				S.T.	L.P.		
.070 Water proof Tab 	0.2-0.5mm <sup>2</sup> (AWG#24-20)	Ø1.4-2.4mm	Brass/Pre-tin	<b>171631-1</b>	<b>173600-1</b>	<b>91563-1</b> (411-5254)	
			Brass/Sel. Gold	<b>171631-2</b>	—		
	0.5-1.25mm <sup>2</sup> (AWG#20-16)	Ø2.0-2.6mm	Brass/Pre-tin	<b>171661-1</b>	<b>173706-1</b>	<b>91585-1</b> (411-5322)	
			Brass/Sel. Gold	<b>171661-2</b>	—		
Crimp Specifications : 114-5082							
.070 Water proof Receptacle 	0.2-0.5mm <sup>2</sup> (AWG#24-20)	Ø1.4-2.4mm	Brass/Pre-tin	<b>171630-1</b>	<b>171699-1</b>	<b>91563-1</b> (411-5254)	
			Copper Alloy/Sel. Gold	<b>171630-5</b>	—		
	0.5-1.25mm <sup>2</sup> (AWG#20-16)	Ø2.0-2.6mm	Brass/Pre-tin	<b>171662-1</b>	<b>173707-1</b>	<b>91583-1</b> (411-5322)	
			Copper Alloy/Pre-tin	<b>171662-4</b>	—		
			Copper Alloy/Sel. Gold	<b>171662-5</b>	—		
	Crimp Specifications : 114-5082						

## Rubber Plug and Cavity Plug

Description	Style	Wire Ins. Diameter	Material/Color	Part No.
Rubber Plug (S Size)		Ø1.4-2.4mm	NBR/Black	<b>172746-1</b>
		Ø1.4-2.1mm	NBR/Black	<b>178210-1</b>
Rubber Plug (M Size)		Ø2.0-2.6mm	NBR/Gray	<b>172888-2</b>
			Silicon/Brown	<b>1-172888-3</b>
		Ø1.8-2.6mm	NBR/Gray	<b>176886-2</b>
Cavity Plug		—	NBR/Black	<b>172748-1</b>
			NBR/Gray	<b>172748-2</b>