

# MINI MATE® CONNECTOR SET IPT1, IPS1

## SPECIFICATIONS

For complete specifications see [www.samtec.com?IPT1](http://www.samtec.com?IPT1) or [www.samtec.com?IPS1](http://www.samtec.com?IPS1)

**Insulator Material:** Black LCP  
**Contact Material:** Phosphor Bronze



**Plating:** Sn or Au over 50µ" (1.27µm) Ni

**Operating Temp Range:**

-55°C to +105°C with Tin;

-55°C to +125°C with Gold

**Insertion Depth:** (3.71mm)

.146" to (6.48mm) .255"

**Wiping Distance:**

(0.38mm) .015"

**Insertion Force (SMT):**

3.0oz (0.83N) avg.

**Withdrawal Force (SMT):**

2.6oz (0.72N) avg.

**Insertion Force (T/H):**

6.0oz (1.67N) avg.

**Withdrawal Force (T/H):**

5.0oz (1.39N) avg.


**Voltage Rating:** 550 VAC

**RoHS Compliant:** Yes

CURRENT RATING	
AMBIENT TEMP	IPT1/IPS1
20°C	8A
40°C	7.2A
60°C	6A
95°C	4.1A

6 POSITIONS (2x3)

**APPLICATION SPECIFIC OPTION**  
 Latching feature available. Call Samtec.



**Processing:**  
**Max Processing Temp:** 230°C for 60 seconds, or 260°C for 20 seconds 3x  
**Lead-Free Solderable:** Yes  
**SMT Lead Coplanarity:** (0.13mm) .005" max (05-10) (0.15mm) .006" max (15-25)

**Note:** Other Gold plating options available. Contact Samtec.  
**Note:** Some sizes, styles and options are non-standard, non-returnable.

**IPT1** - **1** NO. PINS PER ROW - **LEAD STYLE** - **PLATING OPTION** - **D** - **TAIL OPTION** - **OTHER OPTION**

Mates with: **IPS1**

**05, 10, 15, 20, 25**  
(Call Samtec for other sizes)

Specify **LEAD STYLE** from chart

**-S**  
= 30µ" (0,76µm)  
Gold on contact, Matte Tin on Tail

Requires **-01** Lead Style (Leave blank for Through-Hole)

**-RA**  
= Right Angle

**-VS**  
= Surface Mount

**-K**  
= (6,00mm) .236" DIA  
Polyimide film Pick & Place Pad (-VS only)

**-LC**  
= Locking Clip (-VS only) (N/A with -A)

**-A**  
= Alignment Pin (-VS only) (N/A with -LC)

**-POL**  
= No. 1 position polarized

LEAD STYLE	A	B	C
-01	(11,05) .435	(5,84) .250	(2,16) .085
-01-VS	(13,59) .535	(5,84) .250	N/A
-02	(14,00) .551	(9,30) .366	(2,64) .104
-03	(16,00) .630	(11,30) .445	(2,16) .085
-04	(17,00) .669	(12,30) .484	(2,69) .106
-05	(19,00) .748	(14,30) .563	(2,46) .097
-06	(20,00) .787	(15,30) .602	(2,35) .093
-07	(25,00) .984	(20,30) .799	(2,31) .091
-08	(30,00) 1.181	(25,30) .996	(2,39) .094
-09	(35,00) 1.378	(30,30) 1.193	(2,46) .097

**IPS1** - **1** NO. PINS PER ROW - **01** - **PLATING OPTION** - **D** - **TAIL OPTION** - **OTHER OPTION** - **POL OPTION**

Mates with: **IPT1**

**05, 10, 15, 20, 25**  
(Call Samtec for other sizes)

**-S**  
= 30µ" (0,76µm)  
Gold on contact, Matte Tin on Tail

Leave blank for Through-hole

**-VS**  
= Surface Mount

**-RA**  
= Right Angle

**-K**  
= (5,50mm) .217" DIA  
Polyimide film Pick & Place Pad (-VS only)

**-LC**  
= Locking Clip (-VS only)

**-POL**  
= No. 1 position polarized

**-TR**  
= Tape & Reel Packaging

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047  
 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299  
 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 • Fax: 65 6841-1502  
 SAMTEC HONG KONG • Tel: 852-2600-4850 • Fax: 852-2600-4841  
 SAMTEC JAPAN • Tel: 045-475-1385 • Fax: 045-475-1340  
 SAMTEC KOREA • Tel: 82-31-717-5685 • Fax: 82-31-717-5681  
 SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520  
 SAMTEC FRANCE • Tel: 33 01 60 95 06 60 • Fax: 33 01 60 95 06 61  
 SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-5423 4575  
 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112 • Fax: 27 86 6714432  
 SAMTEC UK • Tel: 44 01236 739292 • Fax: 44 01236 727113  
 SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315  
 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 • Fax: +46-87420413  
 SAMTEC ISRAEL • Tel: 972-3-7526600 • Fax: 972-3-7526690  
 SAMTEC INDIA • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187  
 SAMTEC TAIWAN • Tel: 886-2-2735-6109 • Fax: 886-2-2735-5036  
 SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745