






IPBS-105-H2-T-D



IPBS-110-01-T-D-GP



IPBS-105-01-T-S-GP



POWER MATE™ SOCKET IPBS SERIES

SPECIFICATIONS

For complete specifications see www.samtec.com?IPBS

Insulator Material:
Black Liquid Crystal Polymer



Contact Material:
-01= Phosphor Bronze
-H1= High Copper Alloy

Plating:
Sn over 50µ" (1,27µm) Ni
Operating Temp Range:
-40°C to +105°C

Insertion Depth:
(6,15mm) .242" to
(7,24mm) .285"

Wiping Distance:
(0,38mm) .015" min.

Insertion Force:
14oz (3,89N) avg.

Withdrawal Force:
10oz (2,78N) avg.

Voltage Rating:
725 VAC

RoHS Compliant:
Yes

Processing:


Max Processing Temp:
230°C for 60 seconds, or
260°C for 20 seconds 3x
Lead-Free Solderable:
Yes

Mates with:
IPBT

Individually
shrouded contacts

Optional
polarized
guide posts


AMBIENT TEMP	CURRENT RATING (-HX)	
	2 PINS	4 PINS
20°C	19.3A	16.6A
40°C	16.9A	14.4A
60°C	14A	12A
75°C	11.4A	9.7A



(4,19mm)
.165"
pitch



IPBS	1	NO. OF POSITIONS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	OPTION
		02, 03, 04, 05, 10, 15 (-D only)	-01 = Standard Power -02 = Standard Power Surface Mount -H1 = High Power -H2 = High Power Surface Mount	-T = Matte Tin	-S = Single Row -D = Double Row	-GP = Guide Post
		02, 03, 04, 05 (-S only) (Call Samtec for other sizes)				



Note: Some lengths, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047
 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299
 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 • Fax: 65 6841-1502
 SAMTEC HONG KONG • Tel: 852-2800-4850 • Fax: 852-2800-4841
 SAMTEC FRANCE • Tel: 01 60 95 06 60 • Fax: 01 60 95 06 61
 SAMTEC SOUTH AFRICA • Tel: 27 11 452 8112 • Fax: 27 86 6714432
 SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520
 SAMTEC ISRAEL • Tel: 972-3-7526600 • Fax: 972-3-7526690
 SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-5423 4575
 SAMTEC UK • Tel: 01236 739292 • Fax: 01236 727113
 SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315
 SAMTEC INDIA • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187
 SAMTEC TAIWAN • Tel: 886-2-2735-6109 • Fax: 886-2-2735-5036
 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 • Fax: +46-87420413
 SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745