Our commitment. Your advantage.

Search

Products

Documentation


Resources

My Account

Customer Support

Home > Products > By Type > Product Feature Selector > Product Details

964274 - 2 Product Details



964274 - 2



Timer Contacts

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- ? Contact
- ? Contact Type = Micro Timer II
- Receptacle
- Wire Range = 0.50 -1.00 ² [20-17] mm [AWG]
- ? Insulation Diameter = 1.40 2.10 mm

<u>View all Features</u> | <u>Find Similar</u> <u>Products</u>

Live Product Chat US Only 8:30am - 5pm ET, Mon - Fri

Quick Links

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

- ? MICRO TIMER 2 CONTACT TYP A (PDF, English)
- PRODUCT GROUP DRAWING FOR MICRO TIMER 2 CONTACT TYP <u>A</u> (PDF, German)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

2 EG**Micro Timer 2 Kontakt (PDF, English)

Application Specifications:

- APPLICATION SPECIFICATION FOR: (Specifica di applica... (PDF English)
- ? Micro Timer 2+3 Contact (PDF, German)

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

Product Line Information

Additional Product Images:

2 Line Drawing

Related Products:

? Tooling

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Contact
- ? Gender = Receptacle
- Insulation Diameter (mm [in]) = 1.40 2.10
 [0.055 0.083]
- ? Tab Fit (mm [in]) = $1.60 \times 0.61 [.063 \times .024]$
- ? Comment = Modified Cantilever Springs

Body Related Features:

- Wire Range (mm [AWG]) = 0.50 -1.00 ² [20-17]
- ? Single Wire Sealing System = Yes
- ? Insulation Type = FLK, FLR
- ? Cantilever Spring Material = Stainless Steel

Contact Related Features:

- ? Contact Type = Micro Timer II
- ? Contact Material = CuFe2
- ? Contact Mating Area Plating Material = Pre -Tin

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

? Terminate To = Wire

Packaging Related Features:

- Packaging Method = Strip
- Packaging Quantity = 4,000

Other:

- ? GET 0.64 Connector System = No
- ? Brand = AMP

Provide Website Feedback | Contact Customer Support