


UMCC — Ultraminiature Coax Connector and Cable Assembly Series

Product Facts

- Ultra low profile (2.0 mm or 2.5 mm maximum mated height)
- Easy snap on/off mating
- Small footprint on PCB (3 mm x 3 mm)
- Excellent performance to 6 GHz
- Surface mount and reflow solderable
- Available on 0.80 mm and 1.37 mm dia. single shield, and 1.32 mm dia. double shield cable
- Style A receptacles mate with HIROSE U.FL/U.FL(v) Series connectors
- Style B receptacles mate with MURATA GSC Series connectors



Description

- Extremely low profile
- Surface mount technology
- 360° mated rotation
- Excellent price-to-performance ratio

Applications

- Wireless LAN, Mini PCI
- Mobile Antenna/GPS/Radio Systems
- PDA/PCS/Cellular Handset applications
- Wireless Communications systems (LAN, GSM, PCS, WCDMA, UMTS)
- Remote measuring equipment

Electrical Characteristics

- Characteristic Impedance** — 50 Ohms
- Frequency Range** — DC to 6 GHz
- VSWR (mated pair)** — 1.30 max. DC to 3 GHz
1.40 max. 3 to 6 GHz (cable dependent)
- Insertion Loss (connectors only)** — 0.24 dB max. DC to 6 GHz
- Rated Voltage** — 60 VAC (rms) — standard receptacle (Styles A, B)
- Dielectric Withstanding Voltage** — 200 VAC, 50 Hz for 1 min. @ sea level
- Insulation Resistance** — 500 Megohms min.
- Contact Resistance (connectors only)** — 20 milliohms max. (Center)
10 milliohms max. (Outer, Plug)
10 milliohms max. (Outer, Receptacle)

Mechanical and Environmental Characteristics

- Durability** — 30 cycles — standard receptacle (Styles A, B)
- Disengagement Force** — 2N min. perpendicular
4N min. orthogonal
- Center Contact Retention Force** — 0.15N min.
- Tape/Reel Packaging (receptacle)** — 12 mm carrier per EIA-481
- Operating Temperature** — -40°C to +90°C

Material and Finish

- Shell** — Phosphor bronze, plated gold or silver
- Male Center Contact** — Brass or phosphor bronze, plated gold
- Female Center Contact** — Brass or phosphor bronze, plated gold
- Insulator (Plug)** — PBT (15% G.F.), black, UL94V-0
- Insulator (Receptacle)** — LCP, beige or black, UL94V-0

Related Product Data

- Product Specification** — 108-2231
- Sample Kit** — 1-1773441-6

HIROSE is a trademark of Hirose Electric.
MURATA is a trademark of Murata Electronics, Inc.

UMCC — Ultraminiature Coax Connector and Cable Assembly Series (Continued)

Cable Information

Material and Finish

Center Conductor —
0.8 mm Dia. — Silver plated copper
1.32 mm Dia. — Silver plated copper
1.37 mm Dia. — Silver plated copper

Center Conductor Size —
0.8 mm Dia. — Stranded 7/0.05 mm
1.32 mm Dia. — Stranded 7/0.08 mm
1.37 mm Dia. — Stranded 7/0.10 mm

Dielectric —
0.8 mm Dia. — FEP or PFA
1.32 mm Dia. — FEP
1.37 mm Dia. — FEP

Dielectric Size —
0.8 mm Dia. — 0.4 mm OD
1.32 mm Dia. — 0.66 mm OD
1.37 mm Dia. — 0.83 mm OD

Shield —
0.8 mm Dia. — Silver plated copper braid
1.32 mm Dia. — Double SPL braid
1.37 mm Dia. — Silver plated copper braid

Shield Coverage —
0.8 mm Dia. — > 90%
1.32 mm Dia. — > 90% (each braid layer)
1.37 mm Dia. — > 90%

Jacket —
0.8 mm Dia. — FEP or PFA
1.32 mm Dia. — FEP
1.37 mm Dia. — FEP

Jacket Size —
0.8 mm Dia. — 0.80 mm OD
1.32 mm Dia. — 1.32 mm OD
1.37 mm Dia. — 1.37 mm OD

Mechanical Characteristics

Minimum Bend Radius —
0.8 mm Dia. — 5 mm single bend, 30 mm continuous flexing
1.32 mm Dia. — 5 mm single bend, 30 mm continuous flexing
1.37 mm Dia. — 5 mm single bend, 30 mm continuous flexing

Electrical Characteristics


Impedance (Ohms) —
0.8 mm Dia. — 50 ± 2
1.32 mm Dia. — 50 ± 2
1.37 mm Dia. — 50 ± 2

Velocity of Propagation —
0.8 mm Dia. — 70%
1.32 mm Dia. — 70%
1.37 mm Dia. — 70%


CC Resistance (Ohms/KM) —
0.8 mm Dia. — 1450
1.32 mm Dia. — 560
1.37 mm Dia. — 354

Voltage Rating —
0.8 mm Dia. — 60 VAC
1.32 mm Dia. — 60 VAC
1.37 mm Dia. — 60 VAC

Attenuation — See chart




UMCC Cable Attenuation






UMCC — Ultraminiature Coax Connector and Cable Assembly Series (Continued)

**PCB Receptacles —
Style A**




| Style | Mates with UMCC Connector Type | Mated Height (H) | Description | Part Number |
|-------|--------------------------------|------------------------|-----------------------------------|-------------|
| A | II / III | 2.00–2.50 .079–.098 | UMCC PCB Receptacle, 2500 Pc Reel | 1566230-1 |
| A | II / III | 2.00–2.50 .079–.098 | UMCC PCB Receptacle, 500 Pc Bag | 1566230-2 |

UMCC PCB Receptacle






Recommended PC Board Layout

**PCB Receptacles —
Style B**



| Style | Mates with UMCC Connector Type | Mated Height (H) | Description | Part Number |
|-------|--------------------------------|------------------|-----------------------------------|-------------|
| B | I | 2.00 .079 | UMCC PCB Receptacle, 2500 Pc Reel | 1775146-1 |
| B | I | 2.00 .079 | UMCC PCB Receptacle, 500 Pc Bag | 1775146-2 |

UMCC PCB Receptacle




Recommended PC Board Layout


Note: Part Numbers are RoHS compliant except: ♦ Indicates non-RoHS compliant.

UMCC — Ultraminiature Coax Connector and Cable Assembly Series (Continued)

Standard Double Ended Cable Assemblies



| UMCC Connector Type | Mated Height (H) | Cable Dia. | Length L | Mates with PCB Rcpt. | Part Number |
|---------------------|------------------|--------------|-----------------|----------------------|-------------|
| I | 2.00 .079 | 0.80 .031 | 100.00 3.937 | Style B | 1750109-1 |
| | 2.00 .079 | 0.80 .031 | 200.00 7.874 | Style B | 1750109-2 |
| II | 2.00 .079 | 0.80 .031 | 100.00 3.937 | Style A | 1750108-1 |
| | 2.00 .079 | 0.80 .031 | 200.00 7.874 | Style A | 1750108-2 |
| III | 2.50 .098 | 0.80 .031 | 100.00 3.937 | Style A | 1750107-1 |
| | 2.50 .098 | 0.80 .031 | 200.00 7.874 | Style A | 1750107-2 |
| | 2.50 .098 | 1.32 .052 | 100.00 3.937 | Style A | 1750107-3 |
| | 2.50 .098 | 1.32 .052 | 200.00 7.874 | Style A | 1750107-4 |
| III | 2.50 .098 | 1.37 .054 | 100.00 3.937 | Style A | 1750107-5 |
| | 2.50 .098 | 1.37 .054 | 200.00 7.874 | Style A | 1750107-6 |



Note: Part Numbers are RoHS compliant except: ♦ Indicates non-RoHS compliant.


UMCC — Ultraminiature Coax Connector and Cable Assembly Series (Continued)

Interseries Cable Assemblies




| UMCC Connector Type | Mated Height (H) | Cable Dia. | Length | Description | Part Number |
|---------------------|------------------|--------------|-----------------|------------------------------------|-------------|
| III | 2.50 .098 | 1.37 .054 | 200.00 7.874 | UMCC Plug to FME Plug | 1750110-2 |
| | 2.50 .098 | 1.37 .054 | 200.00 7.874 | UMCC Plug to SMA Plug | 1750110-4 |
| | 2.50 .098 | 1.37 .054 | 200.00 7.874 | UMCC Plug to SMA Bulkhead Jack | 1750110-6 |
| | 2.50 .098 | 1.37 .054 | 200.00 7.874 | UMCC Plug to MCX Right-Angle Plug | 1750110-8 |
| | 2.50 .098 | 1.37 .054 | 200.00 7.874 | UMCC Plug to MMCX Right-Angle Plug | 1-1750110-0 |
| II | 2.00 .079 | 0.80 .031 | 200.00 7.874 | UMCC Plug to MCX Right-Angle Plug | 1750110-7 |
| | 2.00 .079 | 0.80 .031 | 200.00 7.874 | UMCC Plug to MMCX Right-Angle Plug | 1750110-9 |


UMCC to FME Plug




UMCC to SMA Plug




UMCC to SMA Bulkhead Jack



UMCC to MCX Right-Angle Plug



UMCC to MMCX Right-Angle Plug




Note: Part Numbers are RoHS compliant except: ♦ Indicates non-RoHS compliant.

UMCC — Ultraminiature Coax Connector and Cable Assembly Series (Continued)



Adapters





| UMCC Connector Type | Description | Part Number |
|---------------------|----------------------------------|-------------|
| I | UMCC Jack Receptacle to SMA Plug | 1775228-1 |
| | UMCC Plug to SMA Jack | 1775229-1 |
| II / III | UMCC Jack Receptacle to SMA Plug | 1775227-1 |
| | UMCC Plug to SMA Jack | 1775230-1 |





Part Number 1775228-1




Part Number 1775227-1




Part Number 1775229-1



Part Number 1775230-1





Extraction Tool
Part Number 1775231-1



Note: Part Numbers are RoHS compliant except: ♦ Indicates non-RoHS compliant.

UMCC — Ultraminiature Coax Connector and Cable Assembly Series (Continued)

Application Notes
Mating/Unmating — Cable Plugs



Mating/Unmating


1. To mate the connectors, insert the cable plug into the SMT receptacle, making sure the cable plug is as vertical as possible and the mating axis of both connectors are aligned. Do not insert on an extreme angle.
2. To unmate the connectors, insert the end portion of the extraction tool under the SMT receptacle connector flanges and pull off vertically in the direction of the mating axis.

Permissible Load


Do not apply excessive load to the cable after the connectors are mated. Please refer to the permissible loads indicated in the figure to the right.

Tape and Reel Packaging Specifications

Standard Receptacles



Dimensions of Taping



Dimensions Reel (2500 Pieces/Reel)

Soldering Profile — SMT Receptacle

Recommended Temperature Profile (Reference)

1. The preferred technique for mounting the SMT Receptacle package is to reflow solder the device onto a PCB (Printed Circuit Board).
2. The maximum temperature for the lead of PCB surface does not exceed 240°C.
3. The right reflow soldering profile is for reference and will modify under individual different conditions.

Hand Soldering (Reference only)

1. Soldering iron: The maximum temperature is 240°C.
2. Soldering period: within 5 seconds.

