

1060464-1 Product Details

[Live Product Chat](#)



1060464-1

TE Part Number: 1060464-1

[Active](#)

[Add to Part List](#)

SMB RF Connectors

[Always EU RoHS/ELV Compliant](#) (Statement of Compliance)

Product Highlights:

- Connector
- Jack
- Standard
- Terminate To Printed Circuit Board
- Coupler Style = Quick Connect/Disconnect

[View all Features](#) | [Find Similar Products](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

NEW!

Documentation & Additional Information

Product Drawings:

- [SMB RIGHT ANGLE PRINTED CIRCUIT BOARD JACK RECEPTAC...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Connector
- [Gender](#) = Jack
- Connector Series = Standard
- [Body Style](#) = Right Angle
- [Grade](#) = Commercial
- [PCB Mount Angle](#) = Right Angle
- [Board Standoff](#) = With
- PCB Mount Style = Thru Hole
- Profile = Standard
- Dielectric Material = PTFE Fluorocarbon

Mechanical Attachment:

- [Panel Attachment](#) = Without

Electrical Characteristics:

- [Connector Impedance \(Ω\)](#) = 50
- Environmental Seal = Without

Body Related Features:

- Coupler Style = Quick Connect/Disconnect
- [Pin Protection](#) = Without
- Solder Lug = Without
- [Body Plating](#) = Gold

Contact Related Features:

- [Center Contact Plating](#) = Gold
- Contacts = With

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- [Terminate To](#) = Printed Circuit Board

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Need Help?](#)