

Product Details for 413990 - 3



413990 - 3

[Active](#)

SMB RF Connectors

[RoHS Compliant \(Statement of Compliance\)](#)

Product Highlights:

- ? Connector
- ? Jack
- ? Standard
- ? Terminate To Printed Circuit Board
- ? Coupler Style = Quick Connect/Disconnect

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [JACK, RCPT, STR, SMB/PCB](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? [AMP* SMB PRINTED CIRCUIT \(PC\) BOARD VERTICAL JACK CO...](#) (PDF, English)

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Additional Product Images:

- ? [PCB Layout](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Product Type](#) = Connector
- ? [Gender](#) = Jack
- ? Connector Series = Standard
- ? [Body Style](#) = Straight
- ? [Grade](#) = Military
- ? [PCB Mount Angle](#) = Vertical
- ? Board Standoff = Without
- ? PCB Mount Style = Thru Hole
- ? Dielectric Material = TEFLON

Mechanical Attachment:

- ? [Panel Attachment](#) = Without

Electrical Characteristics:

- ? [Connector Impedance \(?\)](#) = 50
- ? Environmental Seal = Without

Body Related Features:

- ? Coupler Style = Quick Connect/Disconnect
- ? [Pin Protection](#) = Without
- ? Solder Lug = Without
- ? [Body Plating](#) = Nickel

Contact Related Features:

- ? [Center Contact Plating](#) = Gold (50)
- ? Contacts = With

Industry Standards:

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in -Paste capable to 245°C, Pin in -Paste capable to 260°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- ? [Terminate To](#) = Printed Circuit Board

Other:

- ? Brand = AMP