<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>RF & Coax</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

# **Product Details for 1052897**

No Image Available

Active

1052897

-1

052697 - 1

# **SMA/QMA RF Connectors**

RoHS Compliant (Statement of Compliance)

## **Product Highlights:**

- ? Connector
- ? Jack
- Connector Type = SMA
- ? Terminate To Printed Circuit Board
- ? Body Style = Straight

View all Features

## **Quick Links**

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

# **Documentation & Additional Information**

## **Product Drawings:**

OSM 4 HOLE FLANGE MOUNT JACK RECEPTACLE -TAB TERMINAL (PDF, English)

### Catalog Pages/Data Sheets:

None Available

#### **Product Specifications:**

None Available

## **Application Specifications:**

? None Available

## **Instruction Sheets:**

None Available

# **CAD Files:**

? None Available

#### Additional Information:

? Product Line Information

#### Related Products:

? Tooling

# Product Features (Please use the Product Drawing for all design activity)

#### **Product Type Features:**

- ? Product Type = Connector
- ? Gender = Jack
- ? Connector Type = SMA
- ? Body Style = Straight
- ? Number of Panel Mount Holes = 4
- ? PCB Mount Angle = Vertical
- ? Body Material = Stainless Steel
- ? Body Finish = Gold
- ? Center Contact = With
- ? Terminal Type = Tab
- ? Tab Width (mm [in]) = 0.51 [0.02]
- ? Dielectric Material = TFE Fluorocarbon

# **Mechanical Attachment:**

- ? Panel Attachment = With
- ? Panel Attachment Method = Flange
- ? Panel Attachment Style = Front Mount
- ? Impedance (?) = 50

#### **Body Related Features:**

List all Documents

Length (mm [in]) = 12.10 [0.476]

# Contact Related Features:

- ? Center Contact Material = Beryllium Copper
- ? Center Contact Plating = Gold

# **Industry Standards:**

- ? Government/Industry Qualification = No
- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in-Paste capable to 245°C, Pin in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

## Conditions for Usage:

? Terminate To = Printed Circuit Board

#### Other:

? Brand = AMP

 Languages
 : English |
 Deutsch |
 Español |
 Português (do Brasil) |
 ??????? |
 Italiano |
 ???? (?? ) |
 ??? (? ? ) |
 ???

 Country Sites |
 : China |
 Japan |