HUBER+SUHNER® DATA SHEET Cable terminator: 83_CT-0-2-3/-11_N



Description

Straight PCB cable terminator for flexible cable

Technical Data

Electrical Data

Not defined Impendance

Mechanical Data

Cable entry crimp

Environmental Data

Operating Temperature -65 to 165°C 2002/95/EC (RoHS) compliant

Material Data

Piece Parts Material **Surface Plating**

Outer contact Brass Body Brass Crimp ferrule Copper

Related Documents

Outline drawing DOU-00013343 Assembly instruction DOC-0000193849

Order Information

Single package 83_CT-0-2-3/-11_NE

Additional Information

Suitable cable RG 316 /U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

Document: 83_CT-0-2-3/-11_N **Uncontrolled Copy** Page1/1 Issued: 24.09.2007



SUCOPRO SUCOPRO

Gold

HUBER+SUHNER AG RF Technlogy 9100 Herisau, Switzerland Phone +41 (0)71 353 41 11

Fax +41 (0)71 353 45 90 www.hubersuhner.com