

# HUBER+SUHNER® DATA SHEET

## Cable terminator: 86\_CT-0-2-5/111\_N



### Description

Straight PCB cable terminator for flexible cable

### Technical Data

#### Electrical Data

Impedance Not defined

#### Mechanical Data

Cable entry soldered

#### Environmental Data

Operating Temperature -65 to 165°C  
2002/95/EC (RoHS) compliant

### Material Data

#### Piece Parts

	Material
Center contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE



#### Surface Plating

SUCOPRO  
SUCOPRO  
SUCOPRO

### Related Documents

Outline drawing DOU-00012698  
Assembly instruction DOC-0000192794

### Order Information

Bulk 100 pcs package 86\_CT-0-2-5/111\_NH

### Additional Information

Suitable cable RG\_316\_/U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com