

# HUBER+SUHNER® DATA SHEET

## Between Series Adapter: 33\_BNC-SMC-50-2/1--\_N

Rev.: C



### Description

Adaptor plug/jack  
BNC plug (male) / SMC jack (female)

Interface standards  
IEC 60169-8\_MIL-STD-348A/301\_CECC 22120



### Technical Data

#### Electrical Data

Impedance	50 Ω
Interface frequency max.	4 GHz
Frequency range	DC to 4 GHz
Return loss	≥ 20 dB

#### Mechanical Data

Number of matings	500
Weight	0.0112 kg

#### Environmental Data

Operating Temperature 2002/95/EC (RoHS)	-65 °C to 165 °C compliant
--	-------------------------------

#### Material Data

##### Piece Parts (BNC)

Piece Parts (BNC)	Material
Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)

##### Surface Plating

Gold Plating (without Nickel underplating)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

##### Piece Parts (SMC)

Piece Parts (SMC)	Material
Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE

##### Surface Plating

Gold Plating (without Nickel underplating)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)

### Related Documents

#### Ordering Information

Single package	33_BNC-SMC-50-2/1--_NE
----------------	------------------------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com