

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_N-50-2-1/133_N

Rev.: B



Description

Straight cable plug

Interface Standards
IEC 61169-16_MIL-STD-348A/304_CECC 22210



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 11 GHz

Mechanical Data

Centre contact soldered
Outer contact clamped
Weight 0.0352 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

| | |
|----------------|-----------------------|
| Centre contact | Brass |
| Outer contact | Brass |
| Body | Brass |
| Insulator | PFA / PTFE |
| Coupling nut | Brass |
| Gasket | MVQ (Silicone Rubber) |

Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

Related Documents

| | |
|----------------------|----------------|
| Outline drawing | DOU-00006961 |
| Catalogue drawing | DOU-00006959 |
| Assembly instruction | DOC-0000177464 |

Ordering Information

| | |
|----------------------|--------------------|
| Single package | 11_N-50-2-1/133_NE |
| Bulk 100 pcs package | 11_N-50-2-1/133_NH |

Additional Information

Suitable cables RG_316_/U, RG_188_A/U, RG_174_/U, RG 174 /U

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com