

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_QLA-01-2-13/122\_N

Rev.: C



### Description

Straight cable plug

Interface Standards  
NIM-CAMAC-Standard CD/N549



### Technical Data

#### Electrical Data

Impedance other  $\Omega$   
Interface frequency max. 1.4 GHz

#### Mechanical Data

Centre contact crimped  
Outer contact crimped  
Weight 0.0031 kg

#### Environmental Data

Operating Temperature -55 °C to 150 °C  
2002/95/EC (RoHS) compliant

#### Material Data

##### Piece Parts

Centre contact  
Outer contact  
Body  
Insulator  
Crimp ferrule

##### Material

Brass  
Brass  
Brass  
PFA / PTFE  
Copper

##### Surface Plating

Gold Plating (Nickel underplated)  
Nickel Plating  
Nickel Plating  
SUCOPLATE (R) Plating

#### Related Documents

Catalogue drawing DOU-00006116  
Assembly instruction DOC-0000179325

#### Ordering Information

Bulk 100 pcs package 11\_QLA-01-2-13/122\_NH

#### Additional Information

Suitable cable G\_01130\_HT-4

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

**HUBER+SUHNER – Excellence in Connectivity Solutions**



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com