

# HUBER+SUHNER® DATA SHEET

## Coaxial Cable Connector: 11\_BNC-75-4-6/133\_N

Rev.: E



### Description

Straight cable plug

Interface Standards  
Interface compatible with IEC 61169-8



### Technical Data

#### Electrical Data

Impedance	75 Ω
Interface frequency max.	1 GHz
Frequency range	DC to 1 GHz
Return loss	≥ 21 dB

#### Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.0103 kg

#### Environmental Data

Operating Temperature	-65 °C to 165 °C
2002/95/EC (RoHS)	compliant

#### Material Data

##### Piece Parts

Centre contact	Brass
Outer contact	Brass
Body	Brass
Insulator	PFA / PTFE
Coupling nut	Brass
Gasket	MVQ (Silicone Rubber)
Crimp ferrule	Copper

##### Material

##### Surface Plating

Gold Plating (Nickel underplated)
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating
SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00071552
Catalogue drawing	DOU-00006189
Assembly instruction	DOC-0000179061

### Ordering Information

Bulk 100 pcs package	11_BNC-75-4-6/133_NH
Single package	11_BNC-75-4-6/133_NE

### Additional Information

Suitable cable	G_04233_D
----------------	-----------

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

#### WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.



**HUBER+SUHNER AG**  
RF Technology  
9100 Herisau, Switzerland  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
www.hubersuhner.com

**HUBER+SUHNER – Excellence in Connectivity Solutions**