

HUBER+SUHNER® DATA SHEET

Coaxial Cable Connector: 11_SMC-50-2-13/111_N

Rev.: A



Description

Straight cable plug

Interface Standards
IEC 60169-9_MIL-STD-348A/312_CECC 22140



Technical Data

Electrical Data

Impedance 50 Ω
Interface frequency max. 10 GHz

Mechanical Data

Centre contact soldered
Outer contact soldered
Weight 0.0018 kg

Environmental Data

Operating Temperature -65 °C to 165 °C
2002/95/EC (RoHS) compliant

Material Data

Piece Parts

Centre contact
Outer contact
Body
Insulator
Coupling nut

Material

Copper Beryllium Alloy
Brass
Brass
PFA / PTFE
Brass

Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)

Related Documents

Outline drawing DOU-00006079
Catalogue drawing DOU-00007227
Assembly instruction DOC-0000179074

Ordering Information

Bulk 100 pcs package 11_SMC-50-2-13/111_NH
Single package 11_SMC-50-2-13/111_NE

Additional Information

Suitable cable EZ_86_TP_M17

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions



HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com