


**6-1337542 -0 Product Details**

**Live Product Chat** US Only  
8:30am - 5pm ET, Mon - Fri



**6-1337542 -0**

[Active](#)

**BNC RF Connectors**

[Always EU RoHS/ELV Compliant](#) ( [Statement of Compliance](#) )

**Product Highlights:**

- ? Connector
- ? Connector Type = ZDC/BNC
- ? Jack
- ? Terminate To Printed Circuit Board
- ? Body Style = Elbow

[View all Features](#) | [Find Similar Products](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

| Documentation & Additional Information  |  |
|---|--|
| <p><b>Product Drawings:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">BNC LOW PROFILE R/A INSULATED PCB SOCKET 50 OHM WHITE</a> (PDF, English)</li> </ul> <p><b>Catalog Pages/Data Sheets:</b></p> <ul style="list-style-type: none"> <li>? None Available</li> </ul> <p><b>Product Specifications:</b></p> <ul style="list-style-type: none"> <li>? None Available</li> </ul> <p><b>Application Specifications:</b></p> <ul style="list-style-type: none"> <li>? None Available</li> </ul> <p><b>Instruction Sheets:</b></p> <ul style="list-style-type: none"> <li>? None Available</li> </ul> <p><b>CAD Files:</b></p> <ul style="list-style-type: none"> <li>? None Available</li> </ul> | <p><b>Additional Information:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Product Line Information</a></li> </ul> <p><b>Related Products:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Tooling</a></li> </ul> |

[List all Documents](#)

| Product Features <small>(Please use the Product Drawing for all design activity)</small>  |  |
|---|--|
| <p><b>Product Type Features:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Product Type</a> = Connector</li> <li>? Connector Type = ZDC/BNC</li> <li>? <a href="#">Gender</a> = Jack</li> <li>? Body Style = Elbow</li> <li>? <a href="#">PCB Mount Angle</a> = Right Angle</li> <li>? <a href="#">Grade</a> = Commercial</li> <li>? <a href="#">PCB Height (mm [in])</a> = 13.16 [0.518]</li> <li>? <a href="#">PCB Retention Feature</a> = Yes</li> <li>? Mounting Post Style = Round</li> <li>? Mounting Post Length (mm [in]) = 3.70 [0.146]</li> <li>? <a href="#">Body Material</a> = Zinc</li> <li>? <a href="#">Body Insulation</a> = With</li> <li>? <a href="#">Sealed</a> = No</li> <li>? <a href="#">Isolated</a> = Yes</li> <li>? <a href="#">Dielectric Material</a> = Polyethylene</li> <li>? <a href="#">Color</a> = White</li> <li>? Number of Ports = 1</li> <li>? Panel Thickness (mm [in]) = 1.50 - 5.50 [0.059 - 0.217]</li> <li>? PCB Thickness (mm [in]) = 3.30 [0.130]</li> </ul> <p><b>Mechanical Attachment:</b></p> <ul style="list-style-type: none"> <li>? Surface Mountable = No</li> <li>? <a href="#">Panel Attachment</a> = With</li> <li>? <a href="#">Panel Attachment Method</a> = Bulkhead, Hex Nut</li> <li>? Panel Attachment Style = Rear Mount</li> <li>? Panel Cutout = 12.0mm x 12.9mm D -Shape</li> <li>? Flange and Thread Material = PBT Polyester</li> <li>? Flange and Thread Material Color = White</li> </ul> <p><b>Electrical Characteristics:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Connector Impedance (?)</a> = 50</li> </ul> | <p><b>Body Related Features:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Hardware Included</a> = No</li> <li>? PCB Retention Method = Solder Tail (Pin)</li> <li>? <a href="#">Body Plating</a> = Nickel</li> <li>? <a href="#">Polarized</a> = No</li> <li>? PCB Tail Length (mm [in]) = 4.30 [0.169]</li> </ul> <p><b>Contact Related Features:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Center Contact Material</a> = Brass</li> <li>? <a href="#">Center Contact Plating</a> = Gold</li> </ul> <p><b>Housing Related Features:</b></p> <ul style="list-style-type: none"> <li>? Housing Material = Polyester (PBT)</li> </ul> <p><b>Industry Standards:</b></p> <ul style="list-style-type: none"> <li>? Government/Industry Qualification = No</li> <li>? <a href="#">RoHS/ELV Compliance</a> = RoHS compliant, ELV compliant</li> <li>? <a href="#">Lead Free Solder Processes</a> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C</li> <li>? RoHS/ELV Compliance History = Always was RoHS compliant</li> </ul> <p><b>Conditions for Usage:</b></p> <ul style="list-style-type: none"> <li>? <a href="#">Terminate To</a> = Printed Circuit Board</li> <li>? Operating Temperature (Max.) (°C) = 85</li> </ul> <p><b>Packaging Related Features:</b></p> <ul style="list-style-type: none"> <li>? Packaging Method = Tray</li> <li>? Packaging Quantity = 50</li> </ul> <p><b>Other:</b></p> <ul style="list-style-type: none"> <li>? Brand = Greenpar</li> </ul> |