

**1-1478057 -0 Product Details**



**1-1478057 -0**

[Active](#)

**BNC RF Connectors**

[Converted to EU RoHS/ELV Compliant](#) ( [Statement of Compliance](#) )

**Product Highlights:**

- ? Connector
- ? Connector Type = BNC
- ? Jack
- ? Terminate To Coaxial Cable
- ? Coaxial Cable Termination Type = Crimp

[View all Features](#) | [Find Similar Products](#)

**Live Product Chat** US Only  
8:30am - 5pm ET, Mon - Fri

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- ? [BNC BULKHEAD JACK REAR MOUNT CRIMP 75 OHM PSF 1/3M, ...](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- ? None Available

**Product Specifications:**

- ? None Available

**Application Specifications:**

- ? None Available

**Instruction Sheets:**

- ? None Available

**CAD Files:**

- ? None Available

**Additional Information:**

- ? [Product Line Information](#)

**Related Products:**

- ? [Tooling](#)

[List all Documents](#)

**Product Features** (Please use the Product Drawing for all design activity)

**Product Type Features:**

- ? [Product Type](#) = Connector
- ? [Connector Type](#) = BNC
- ? [Gender](#) = Jack
- ? [Crimp Type](#) = Hex
- ? Body Style = Bulkhead
- ? [Grade](#) = Professional
- ? [Body Material](#) = Brass
- ? [Sealed](#) = No
- ? [Isolated](#) = No
- ? [Dielectric Material](#) = PTFE
- ? Number of Ports = 1
- ? Panel Thickness (mm [in]) = 2.00 - 5.00 [0.078 - 0.197]
- ? Flats Dimension = 16.0 A/F
- ? Gasket Material = White Silicone Rubber

**Mechanical Attachment:**

- ? Surface Mountable = No
- ? [Panel Attachment](#) = With
- ? Panel Attachment Method = Hex Nut
- ? Panel Attachment Style = Rear Mount
- ? Panel Cutout = 12.0mm x 12.9mm D -Shape
- ? Flange Dimension [A/F] (mm [in]) = 17.5 [0.689]
- ? Flange and Thread Material = Brass
- ? Lockwasher Material = Mild Steel
- ? Lockwasher Plating = Nickel

**Electrical Characteristics:**

- ? [Connector Impedance \(?\)](#) = 75
- ? Frequency = DC - 2 GHz

**Termination Related Features:**

- ? [Coaxial Cable Termination Type](#) = Crimp

**Body Related Features:**

- ? [Hardware Included](#) = No
- ? [Body Plating](#) = Nickel
- ? [Polarized](#) = No
- ? Ferrule Type = Hex
- ? Hand Tool No. = 9 -1478240 -0
- ? Interchangeable Die Set Number = 9 -1478242 -0
- ? Crimp Dimensions = 1.75 + 2.6 + 5.6 + 6.5

**Contact Related Features:**

- ? [Center Contact Material](#) = Brass
- ? [Center Contact Plating](#) = Gold

**Configuration Related Features:**

- ? [Coaxial Cable Type \(RG/U or Mfg.\)](#) = PSF 1/3M, TM3304

**Industry Standards:**

- ? Government/Industry Qualification = No
- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Converted to comply with RoHS directive

**Conditions for Usage:**

- ? [Terminate To](#) = Coaxial Cable
- ? Operating Temperature (Max.) (°C) = 165

**Packaging Related Features:**

- ? Packaging Method = Individual
- ? Packaging Quantity = 50

**Other:**

- ? Brand = Greenpar