

- Panel Thickness (mm [in]) = 2.40 [0.094]
- Dielectric Material = PTFE
- ? Sealed = No
- Isolated = No
- · Flats Dimension = 11.0 A/F

Mechanical Attachment:

- ? Panel Attachment = With
- ? Panel Attachment Method = Bulkhead
- Panel Attachment Style = Rear Mount
- ? Lockwasher Material = Mild Steel
- ? Lockwasher Plating = Gold
- ? Nut Material = Brass
- Panel Cutout = 6.4 x 6.0 D Shape
- ? Flange Dimensions = 11.0 A/F Hex
- ? Flange and Thread Material = Brass

Electrical Characteristics:

- ? Impedance (?) = 50
- · Frequency = DC 6 GHz

- ? Center Contact Material = Beryllium Copper
- ? Center Contact Plating = Gold

Configuration Related Features:

? <u>Coaxial Cable Type (RG/U or Mfg.)</u> = 402 Semi -Rigid/3.58 [.141]

Industry Standards:

- Government/Industry Qualification = No
 <u>RoHS/ELV Compliance</u> = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Not relevant for lead free process
- ? RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- ? <u>Terminate To</u> = Coaxial Cable
- · Operating Temperature (Max.) (°C) = 165

Packaging Related Features:

- Packaging Quantity = 100
- Other:
 - ? Brand = Greenpar

Home | Customer Support | Suppliers | Site Map | Privacy Policy | Browser Support © 2008 Tyco Electronics Corporation All Rights Reserved