


1 - 1478019 - 0 Product Details

Live Product Chat US Only
8:30am - 5pm ET, Mon - Fri



1 - 1478019 - 0

[Active](#)

TNC RF Connectors

[Converted to EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

Product Highlights:

- ? Connector
- ? Jack
- ? Terminate To Coaxial Cable
- ? Coaxial Cable Termination Type = Wedge -Lock
- ? Coaxial Cable Type (RG/U or Mfg.) = 174A, 188A, 316, Raychem 5026A1318, Raychem 5026A1331, Raychem 5026A1631, Raychem 5026C1309, Raychem 5026D1028, Raychem 5026D1424, Raychem CLFH 316, Raychem EPD 26995Q, URM 95

[View all Features](#) | [Find Similar Products](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- ? [TNC STRAIGHT BULKHEAD JACK SOLDER SILVER PLT 50 OHM...](#) (PDF, English)

Catalog Pages/Data Sheets:

- ? None Available

Product Specifications:

- ? None Available

Application Specifications:

- ? None Available

Instruction Sheets:

- ? None Available

CAD Files:

- ? None Available

Additional Information:

- ? [Product Line Information](#)

Related Products:

- ? [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? [Product Type](#) = Connector
- ? [Gender](#) = Jack
- ? [Body Style](#) = Bulkhead
- ? [Body Material](#) = Brass
- ? Weatherproof = No
- ? [Solder Terminal](#) = Without
- ? Body Shape = Hexagonal
- ? Panel Thickness (mm [in]) = 2.00 - 5.00 [0.078 - 0.197]
- ? Grade = Professional
- ? Flats Dimension = 16.0 A/F
- ? Dielectric Material = PTFE
- ? Gasket Material = White Silicone Rubber
- ? Number of Panel Mount Holes = 1

Mechanical Attachment:

- ? [Panel Attachment](#) = With
- ? Panel Attachment Method = Hex Nut
- ? Panel Attachment Style = Rear Mount
- ? Lockwasher Material = Mild Steel
- ? Lockwasher Plating = Silver
- ? Flange Dimension [A/F] (mm [in]) = 17.5 [0.689]
- ? Panel Cutout = 12.0mm x 12.7mm D -Shape

Electrical Characteristics:

- ? [Connector Impedance \(?\)](#) = 50
- ? Frequency = DC - 11 GHz

Termination Related Features:

- ? [Coaxial Cable Termination Type](#) = Wedge -Lock

Body Related Features:

- ? [Body Plating](#) = Silver

Contact Related Features:

- ? Center Contact Plating = Silver
- ? Center Contact Material = Brass

Configuration Related Features:

- ? [Coaxial Cable Type \(RG/U or Mfg.\)](#) = 174A, 188A, 316, Raychem 5026A1318, Raychem 5026A1331, Raychem 5026A1631, Raychem 5026C1309, Raychem 5026D1028, Raychem 5026D1424, Raychem CLFH -316, Raychem EPD 26995Q, URM 95

Industry Standards:

- ? Government/Industry Qualification = No
- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- ? [Terminate To](#) = Coaxial Cable
- ? Operating Temperature (Max.) (°C) = 165

Packaging Related Features:

- ? Packaging Method = Individual
- ? Packaging Quantity = 50

Other:

- ? Brand = Greenpar