Customer Support

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>RF & Coax</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

6-1337494 - 2 Product Details



6-1337494 -2

BNC RF Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- ? Connector
- ? Connector Type = ZDC/BNC
- ? Jack
- ? Terminate To Printed Circuit Board
- ? Body Style = Elbow

<u>View all Features</u> | <u>Find Similar</u> <u>Products</u>

Live Product Chat US Only

Quick Links

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

2 BNC R/A PCB SHIELDED SOCKET 50 OHM (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

Product Line Information

Related Products:

? Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Product Type = Connector
- ? Connector Type = ZDC/BNC
- ? Gender = Jack
- ? Body Style = Elbow
- ? PCB Mount Angle = Right Angle
- ? Grade = Commercial
- ? PCB Height (mm [in]) = 15.20 [0.598]
- ? PCB Retention Feature = Yes
- Pody Material = Zinc
- ? Sealed = No
- ? <u>Isolated</u> = No
- ? <u>Dielectric Material</u> = Polyethylene
- ? Number of Ports = 1
- Panel Thickness (mm [in]) = 1.50 5.50 [0.059 0.217]
- PCB Thickness (mm [in]) = 3.20 [0.126]
- ? Solder Terminal = With

Mechanical Attachment:

- ? Surface Mountable = No
- ? Panel Attachment = With
- ? Panel Attachment Method = Bulkhead, Hex Nut
- ? Panel Attachment Style = Rear Mount
- Panel Cutout = 12.0mm x 12.9mm D Shape

Electrical Characteristics:

? Connector Impedance (?) = 50

Body Related Features:

- ? <u>Hardware Included</u> = No
- PCB Retention Method = Mounting Holes
- ? Body Plating = Nickel
- ? Polarized = No
- PCB Tail Length (mm [in]) = 4.20 [0.165]

Contact Related Features:

- ? Center Contact Material = Brass
- ? Center Contact Plating = Gold

Industry Standards:

- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

- ? Terminate To = Printed Circuit Board
- Operating Temperature (Max.) (°C) = 85

Packaging Related Features:

- Packaging Method = Tray
- ? Packaging Quantity = 50

Other

Prand = Greenpar

Provide Website Feedback | Contact Customer Support