


Product Details for 1052538 - 1

 <p style="text-align: center;">No Image Available</p> <p style="font-size: 1.2em; font-weight: bold;">1052538 - 1</p> <p style="color: green; font-weight: bold;">✔ Active</p>	<p>SMA/QMA RF Connectors</p> <p>RoHS Compliant (Statement of Compliance)</p> <p>Product Highlights:</p> <ul style="list-style-type: none"> ? Connector ? Jack ? Connector Type = SMA ? Terminate To Printed Circuit Board ? Body Style = Straight <p>View all Features</p>	<p>Quick Links</p> <ul style="list-style-type: none"> Check Pricing & Availability Search for Tooling Product Feature Selector Contact Us About This Product
--	---	---

Documentation & Additional Information	
<p>Product Drawings:</p> <ul style="list-style-type: none"> ? OSSM STRAIGHT PANEL JACK RECEPTACLE (PDF, English) <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> ? None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> ? None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> ? None Available <p>CAD Files:</p> <ul style="list-style-type: none"> ? None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> ? Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> ? Tooling
List all Documents	

Product Features <small>(Please use the Product Drawing for all design activity)</small>	
<p>Product Type Features:</p> <ul style="list-style-type: none"> ? Product Type = Connector ? Gender = Jack ? Connector Type = SMA ? Body Style = Straight ? Number of Panel Mount Holes = 2 ? PCB Mount Angle = Vertical ? Body Material = Stainless Steel ? Body Finish = Passivated ? Center Contact = With ? Retractable Collar = Without ? Safety Wire Holes = Without ? Dielectric Material = TFE Fluorocarbon <p>Mechanical Attachment:</p> <ul style="list-style-type: none"> ? Panel Attachment = With ? Panel Attachment Method = Flange ? Panel Attachment Style = Rear Mount ? Impedance (?) = 50 	<p>Body Related Features:</p> <ul style="list-style-type: none"> ? Length (mm [in]) = 16.00 [0.630] <p>Contact Related Features:</p> <ul style="list-style-type: none"> ? Contact Type = Split Pin ? Center Contact Material = Beryllium Copper ? Center Contact Plating = Gold <p>Industry Standards:</p> <ul style="list-style-type: none"> ? Government/Industry Qualification = No ? RoHS/ELV Compliance = RoHS compliant, ELV compliant ? Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin -in -Paste capable to 245°C, Pin in -Paste capable to 260°C ? RoHS/ELV Compliance History = Always was RoHS compliant <p>Conditions for Usage:</p> <ul style="list-style-type: none"> ? Terminate To = Printed Circuit Board <p>Other:</p> <ul style="list-style-type: none"> ? Brand = AMP