| 7 | Electronics | Our commit | ment. Your advantag | ge. | Search |
|----------|---------------|------------|---------------------|------------------|--------|
| Products | Documentation | Resources | My Account | Customer Support | |

<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>RF & Coax</u> > <u>Product Feature Selector</u> > Product Details

6086274 -1 Product Details

Documentation & Additional Information

| | SMA/QMA RF Connectors | Live Product Chat US Only 8:30am - 5pm ET, Mon - Fri Quick Links |
|-----------------|---|--|
| 6086274 -1 | Always EU RoHS/ELV Compliant (Statement of Compliance) Product Highlights: Connector Jack Connector Type = SMA Without Snap -Lock Terminate To Coaxial Cable | Check Pricing & Availability Search for Tooling Product Feature Selector Contact Us About This Product |
| ✓ <u>Active</u> | View all Features Find Similar Products | |

| Product Drawings: ? SMA, BULKHEAD CABLE JACK, CRIMP ATTACHME (PDF, English) | Additional Information: NT, (2234 -73 ? Product Line Information Related Products: |
|---|---|
| Catalog Pages/Data Sheets: 2 None Available | ? <u>Tooling</u> |
| Product Specifications: 2 None Available | |
| Application Specifications: ? None Available | |
| Instruction Sheets: 2 None Available | |
| CAD Files: 2 None Available | |
| I | List all Documents |
| Product Features (Please use the Product Drawing for all design activity) | |
| Product Type Features: Product Type _ = Connector Gender = Jack Connector Type _ = SMA Crimp Type _ = Compression Body Style _ = Straight Body Material _ = Brass Body Finish _ = White Bronze Center Contact _ = With Retractable Collar _ = Without Dielectric Material = TFE Fluorocarbon Mechanical Attachment: Panel Attachment _ = With Panel Attachment Method _ = Bulkhead Panel Attachment Style _ = Rear Mount Lockwasher Material = Phosphor Bronze Electrical Characteristics: Impedance (?) = 50 Frequency = DC - 6 GHz Insulation Resistance (M?) = 5,000 Termination Related Features: Coaxial Cable Termination Type _ = Crimp | Body Related Features: ? Snap-Lock = Without ? Length (mm [in]) = 26.40 [1.039] ? Shrink Tubing = Without ? Ferrule Material = Copper alloy ? Ferrule Plating = White Bronze Contact Related Features: ? Center Contact Material = Beryllium Copper ? Center Contact Plating = Gold Configuration Related Features: ? Coaxial Cable Type (RG/U or Mfg.) = 174, 188, 316 Industry Standards: ? Government/Industry Qualification = No ? RoHS/ELV Compliance = RoHS compliant, ELV compliant ? Lead Free Solder Processes = Not relevant for lead free process ? RoHS/ELV Compliance History = Always was RoHS compliant Conditions for Usage: ? Terminate To = Coaxial Cable |
| | Other: P Brand = AMP |

Provide Website Feedback | Contact Customer Support

Home | Customer Support | Suppliers | Site Map. | Privacy Policy | Browser Support © 2008 Tyco Electronics Corporation All Rights Reserved