1 - 1337403   - 0 Product Details

N Series RF Connectors

Converted to EU RoHS/ELV Compliant   (Statement of Compliance)

Product Highlights:
- Connector
- Plug
- Coaxial Cable Termination Type = MIL - Clamp
- Terminate To Coaxial Cable
- Coaxial Cable Type (RG/U or Mfg.) = 214, 9B, Raychem 5012A3422, Raychem 5012F3332, Raychem 5012F3832, Raychem 5012M3612, URM 91

View all Features | Find Similar Products

1 - 1337403   - 0

✔ Active

Documentation & Additional Information

Product Drawings:
- TYPE-N STRAIGHT PLUG SOLDER 50 OHM RG9B/U, 214/U, U...
  (PDF, English)

Catalog Pages/Data Sheets:
- None Available

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files:
- None Available

Additional Information:
- Product Line Information

Related Products:
- Tooling

List all Documents

Product Features *(Please use the Product Drawing for all design activity)*

Product Type Features:
- Product Type = Connector
- Gender = Plug
- Body Style = Straight
- Grade = Commercial
- Lightning/EMP Protection = None
- Dielectric Material = PTFE
- Weatherproof = No
- Flats Dimension = 15.8 A/F
- Body Material = Brass
- Gasket Material = White Silicone Rubber
- Coupling Nut Material = Brass

Mechanical Attachment:
- Panel Attachment = Without

Electrical Characteristics:
- Frequency = DC - 11 GHz
- Connector Impedance (?) = 50

Termination Related Features:
- Coaxial Cable Termination Type = MIL   - Clamp

Body Related Features:
- Body Plating = Nickel

Contact Related Features:
- Center Contact Plating = None
- Center Contact Material = Brass

Housing Related Features:
- Captured Center Contact = With

Configuration Related Features:
- Coaxial Cable Type (RG/U or Mfg.) = 214, 9B, Raychem 5012A3422, Raychem 5012F3332, Raychem 5012F3832, Raychem 5012M3612, URM 91

Industry Standards:
- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:
- Terminate To = Coaxial Cable
- Operating Temperature (Max.) (°C) = 165
- Military Style Number = UG   -21D/U

Packaging Related Features:
- Packaging Method = Individual
- Packaging Quantity = 50

Other:
- Brand = Greenpar