Product Details for 1 -1478939 -0



1-1478939

Active

SMA/QMA RF Connectors

RoHS Compliant (Statement of Compliance)

Product Highlights:

- Connector
- Jack
- Connector Type = SMA Terminate To Coaxial Cable
- Coaxial Cable Termination Type = Solder/Clamp

View all Features

Quick Links

Check Pricing & Availability Search for Tooling Product Feature Selector Contact Us About This Product

Documentation & Additional Information

Product Drawings:

SMA STRÄIGHT BULKHEAD, JACK SOLDER PIN, CLAMP ATTAC. (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

None Available

Application Specifications:

None Available

Instruction Sheets:

? None Available

CAD Files:

? None Available

Additional Information:

Product Line Information

Related Products:

? Tooling

List all Documents

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Connector
- ? Gender = Jack
- ? Connector Type = SMA
- ? Body Style = Bulkhead
- ? Number of Panel Mount Holes
- ? Body Material = Stainless Steel
- ? Body Finish = Gold
- ? Center Contact = With
- ? Grade = Professional
- ? Panel Thickness (mm [in]) = 3.20 [0.126]
- ? Dielectric Material = PTFE
- ? Sealed = No
- ? Isolated = No
- ? Flats Dimension = 8.0 A/F

Mechanical Attachment:

- ? Panel Attachment = With
- ? Panel Attachment Method = Bulkhead
- ? Panel Attachment Style = Rear Mount
- ? Impedance (?) = 50
- ? Lockwasher Material = Mild Steel
- ? Lockwasher Plating = Gold
- ? Nut Material = Stainless Steel
- ? Panel Cutout = 6.4 x 6.0 D Shape
- ? Flange Dimensions = 8.0 A/F Hex
- ? Flange and Thread Material = Stainless Steel

Electrical Characteristics:

? Frequency = DC to 18 GHz

Termination Related Features:

Coaxial Cable Termination Type Solder/Clamp

Body Related Features:

- 2 Length (mm [in]) = 18.70 [0.736]
- Polarized = No

Contact Related Features:

- Center Contact Material = Beryllium Copper
- ? Center Contact Plating = Gold

Configuration Related Features:

Coaxial Cable Type (RG/U or Mfg.) 188A, 316, KX 22A, KX 3B, URM 95 = 174A

Industry Standards:

- Government/Industry Qualification = No
- RoHS/ELV Compliance = RoHS compliant, ELV compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Converted to comply with RoHS directive

Conditions for Usage:

- Terminate To = Coaxial Cable
- Operating Temperature (Max.) (°C) = 165

Packaging Related Features:

? Packaging Quantity = 100

Other:

? Brand = Greenpar

 Languages
 : English |
 Deutsch
 Español
 Português (do Brasil)
 ????????
 Italiano
 ????
 (??)
 ??
 ???

 Country Sites
 : China | Japan