<u>Home</u> > <u>Products</u> > <u>By Type</u> > <u>RF & Coax</u> > <u>Product Feature Selector</u> > <u>Product Details</u>

Product Details for 5413476

-6



5413476 - 6

Active

Decoupled BNC RF Connectors

RoHS Compliant (Statement of Compliance)

Product Highlights:

- ? Terminate To Printed Circuit Board
- ? Connector Impedance = 50 ?
- ? Capacitance = 9,400 pF
- ? Without ESD Protection
- ? Voltage Rating = 1500 VDC

View all Features

Quick Links

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

2 JACK, DECOUPLER, VERTICAL, PCB, SERIES BNC (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

PCB Decoupled BNC Straight & Right Angle Jacks (PDF, English)

Application Specifications:

? None Available

Instruction Sheets:

None Available

CAD Files: (CAD Format & Compression Information

- ? 3D Model (STEP, Version B)
- ? 3D Model (IGES, Version B)
- ? 2D Drawing (DXF, Version B)

Additional Information:

? Product Line Information

Related Products:

? Tooling

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? PCB Mount Angle = Vertical
- ? PCB Retention Feature = With
- ? PCB Retention Method Feature = Mounting Post
- ? Clip Style = Standard
- ? Mounting Post Style = Standard
- ? Mounting Post Length (mm [in]) = 4.01 [0.158]
- ? <u>Dielectric Material</u> = Polymethylpentene
- ? Product Type = Connector
- ? Gender = Jack
- ? Grade = Commercial
- ? Body Material = VALOX

Mechanical Attachment:

- ? Panel Attachment = With
- ? Panel Attachment Method = Lockwasher and Nut

Electrical Characteristics:

- ? Connector Impedance (?) = 50
- 2 Capacitance (pF) = 9,400
- ? Voltage Rating (VDC) = 1500

Body Related Features:

? ESD Protection = Without

Contact Related Features:

- ? Center Contact Material = Phosphor Bronze
- ? Center Contact Plating = Gold (30)

Housing Related Features:

? Housing Temperature Rating = Standard

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

? Terminate To = Printed Circuit Board

Other:

? Brand = AMP

 Languages
 : English |
 Deutsch
 Español
 Portuquês (do Brasil)
 ???????
 Italiano
 ????
 (??)
 ?? (? ?)
 ???

 Country Sites
 : China |
 Japan