Our commitment. Your advantage

Products

Documentation

Resources

My Account Customer Support

Home > Products > By Type > RF & Coax > Product Feature Selector > Product Details

9-414244 - 0 Product Details



9-414244 -0

✓ Active



Always EU RoHS/ELV Compliant (Statement of Compliance

Product Highlights:

- ? Connector
- ? Jack
- ? Standard
- ? Terminate To Printed Circuit Board
- ? Coupler Style = Quick Connect/Disconnect

View all Features | Find Similar

Products

Live Product Chat US Only 8:30am - 5pm ET, Mon - Fri

Quick Links

Check Pricing &
Availability
Search for Tooling
Product Feature
Selector
Contact Us About
This Product

Documentation & Additional Information

Product Drawings:

² JACK,RCPT,STR,SMB/PCB (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

? None Available

Application Specifications:

? None Available

Instruction Sheets:

? None Available

CAD Files: (CAD Format & Compression Information)

- 2 2D Drawing (DXF, Version E)
- ? 3D Model (IGES, Version E)
- ? 3D Model_ (STEP, Version E)

Additional Information:

? Product Line Information

Related Products:

? Tooling

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Connector
- ? Gender = Jack
- ? Connector Series = Standard
- ? Body Style = Straight
- ? Grade = Military
- ? PCB Mount Angle = Vertical
- ? PCB Mount Style = Thru Hole
- ? Dielectric Material = TEFLON

Mechanical Attachment:

? Panel Attachment = Without

Electrical Characteristics:

- ? Connector Impedance (?) = 75
- ? Environmental Seal = Without

Body Related Features:

- ? Coupler Style = Quick Connect/Disconnect
- ? Pin Protection = Without
- ? Solder Lug = Without
- ? Body Plating = Tin

Contact Related Features:

- ? Center Contact Plating = Gold over Nickel
- ? Contacts = With

Industry Standards:

- ? RoHS/ELV Compliance = RoHS compliant, ELV compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260° C, Wave solder capable to 265°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

Conditions for Usage:

? <u>Terminate To</u> = Printed Circuit Board

Other:

? Brand = AMP

Provide Website Feedback | Contact Customer Support