

This document was generated on 01/11/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Status:ObsDescription:1.27m	<mark>3052001</mark> solete hm (.050") Pitch Serial ATA Host Receptacle, Through Hole, Right Angle, it 3.50mm (.138"), Top Mount Type, 0.76µm (30µ") Gold (Au) Plating, 22 C Free	
Documents: Drawing (PDF)		Contraction of the second s
General Product Family Series Application Comments Product Name Physical	PCB Receptacles <u>47305</u> Board-to-Board, Signal Top Mount Type Serial ATA	Series image - Reference only  EU ROHS ELV and ROHS Compliant REACH SVHC Not Reviewed
Circuits (Loaded) Durability (mating cycles max Glow-Wire Compliant	No	Low-Halogen Status Not Reviewed Need more information on product
Keying to Mating Part Lock to Mating Part Mated Height Material - Metal Material - Plating Mating Material - Plating Termination Number of Rows Orientation PC Tail Length	Yes None 3.50mm (.138") Brass, Phosphor Bronze Gold Tin 1 Right Angle 2.00mm (.079")	environmental compliance? Email <u>productcompliance@molex.com</u> For a multiple part number RoHS Certificate of Compliance, <u>click here</u> Please visit the <u>Contact Us</u> section for any non-product compliance questions.
PCB Locator PCB Retention PCB Thickness - Recommend Packaging Type Pitch - Mating Interface Plating min - Mating	Embossed Tape on Reel 1.27mm (.050") 0.762µm (30µ")	Search Parts in this Series 47305Series Mates With
Plating min - Termination Polarized to Mating Part Polarized to PCB Surface Mount Compatible (S Temperature Range - Operati Termination Interface: Style		87703
Electrical Current - Maximum per Conta Voltage - Maximum	act 1.5A 15V DC	
Material Info		
Reference - Drawing No Packaging Specification Product Specification Sales Drawing	umbers PK-47305-001 PS-67492-001 SD-47305-200	

This document was generated on 01/11/2011 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

SD-47305-200

Sales Drawing