

This document was generated on 02/01/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: <u>0470821000</u>

Status: Obsolete

Description: 1.27mm (.050") Pitch External Metal-Shielded Serial ATA Plug, Unmated Height

7.70mm (.303"), 0.38 μ m (15 μ ") Gold (Au) Plating, Surface Mount with Shell, Right

Angle, 7 Circuits, with Mylar, Lead Free

Documents:
Drawing (PDF)

General

Product Family I/O Connectors
Series 47082
Application Wire-to-Board

Component Type Plug

Product Name External Serial ATA

Type

Physical

 Boot Color
 N/A

 Circuits (Loaded)
 7

 Circuits (maximum)
 7

 Color - Resin
 Black

 Gender
 Receptacle

 Keying to Mating Part
 Yes

 Lock to Mating Part
 Yes

 Material - Metal
 Copper Alloy

Material - Metal Copp
Material - Plating Mating Gold
Material - Plating Termination Tin
Number of Rows 1

Orientation Right Angle
PCB Locator Yes
PCB Retention Yes

Packaging Type Embossed Tape on Reel

Panel Mount Yes

Pitch - Mating Interface 1.27mm (.050")
Pitch - Termination Interface 1.27mm (.050")
Plating min - Mating 0.381µm (15µ")

Polarized to Mating Part

Polarized to PCB

Ports

Surface Mount Compatible (SMC)

Yes

Yes

Temperature Range - Operating -35°C to +85°C
Termination Interface: Style Surface Mount

Waterproof / Dustproof No

Electrical


Current - Maximum per Contact
Grounding to Panel
Shield Type
Shielded
Yes
Voltage - Maximum
1.5A
Yes
Full Shield
Yes
Voltage - Maximum
15V DC

Solder Process Data

Duration at Max. Process Temperature (seconds) 30

Lead-free Process Capability Reflow Capable (SMT only)

Max. Cycles at Max. Process Temperature



EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Low-Halogen Status
Not Low-Halogen

China RoHS

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
For a multiple part number RoHS Certificate of Compliance, <u>click here</u>

Please visit the <u>Contact Us</u> section for any non-product compliance questions.

Search Parts in this Series

47082 Series

Mates With

68782 External Serial ATA Cable

Assemblies

Process Temperature max. C 255

Material Info

Reference - Drawing Numbers Product Specification PS-47082-001 Sales Drawing SD-47082-001

This document was generated on 02/01/2011

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION