


## 051-0618-0001 Product Details

[Live Product Chat](#)



**051-0618-0001**  
(1466302-1)

TE Part Number: 1466302-1

Active

[Add to Part List](#)

[View 3D PDF](#)

### Twinax and Triax

[Always EU RoHS/ELV Compliant](#) ([Statement of Compliance](#))

#### Product Highlights:

- Connector
- Mating Type = Jack
- Connector Type = Triax
- Coupler Style = Threaded
- Terminate To Coaxial Cable

[View all Features](#) | [Find Similar Products](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files: ([CAD Format & Compression Information](#))

- [2D Drawing](#) (DXF, Version F)
- [3D Model](#) (IGES, Version F)
- [3D Model](#) (STEP, Version F)

[List all Documents](#)

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Type = Connector
- Mating Type = Jack
- [Connector Type](#) = Triax
- Wire Termination Type = Turret
- Body Style = Straight
- Captivated Contacts = With
- Body Material = Brass
- Insulation Material = Teflon

#### Mechanical Attachment:

- Panel Attachment = With
- Panel Attachment Style = Front Mount
- Lockwasher = With
- Panel Attachment Method = Jam Nut

#### Electrical Characteristics:

- Connector Impedance ( $\Omega$ ) = Non-Constant

#### Body Related Features:

- Coupler Style = Threaded
- Body Plating = Silver

#### Contact Related Features:

- Center Contact Material = Brass
- Center Contact Plating = Gold

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C, Reflow solder capable to 245°C, Reflow solder capable to 260°C, Pin-in-Paste capable to 245°C, Pin-in-Paste capable to 260°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Conditions for Usage:

- Terminate To = Coaxial Cable

#### Other:

- Brand = Microdot