

Г

This document was generated on 12/17/2010

## PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: Status: Description:		aneLink™ I/O Latch Receptacle, 4 Lane, InfiniBand™, Cx4 y, Panel Mount, Metal Gasket	
Documents: Drawing (PDF)	Ethemet, a Circuits, Tra	y, Panel Mount, Metal Gasket	
<b>General</b> Product Family Series Application		I/O Connectors <u>91804</u> Wire-to-Board	Series image - Reference only
Comments Component Type Product Name Type		Metal Gasket Receptacle InfiniBand*, LaneLink™ N/A	EU RoHS China RoHS ELV and RoHS Compliant REACH SVHC
<b>Physical</b> Boot Color Circuits (Loaded)		N/A 25	Not Reviewed Low-Halogen Status Not Reviewed Need more information on product
Circuits (maximum) Circuits Detail Color - Resin Durability (mating cycle	es max)	25 8 Differential Pair Black 250	environmental compliance? Email <u>productcompliance@molex.com</u> For a multiple part number RoHS Certificate
Gender Lock to Mating Part Material - Metal Material - Plating Mating		Receptacle Yes Beryllium Copper, Phosphor Bronze, Zinc Alloy Gold	Compliance, <u>click here</u> Please visit the <u>Contact Us</u> section for any non-product compliance questions.
Material - Plating Term Material - Resin Number of Rows		Tin High Temperature Thermoplastic 2	
Orientation PCB Locator PCB Retention PCB Thickness - Reco	mmended	Right Angle Yes Yes 1.60mm (.063"), 2.10mm (.083")	Search Parts in this Series 91804Series Mates With
Packaging Type Panel Mount Pitch - Mating Interface		Tray Yes 1.50mm (.059")	<u>91659</u> , <u>91534</u> , <u>91630</u> , <u>91635</u>
Pitch - Termination Inte Plating min - Mating Plating min - Termination Polarized to Mating Par Polarized to PCB	on	1.50mm (.059") 0.102μm (4μ") 3.048μm (120μ") Yes Yes	<u>91789-0001</u>
Ports Surface Mount Compat Temperature Range - C Termination Interface: S Waterproof / Dustproof	Dperating ´ Style	1 Yes -20°C to +60°C Surface Mount Yes	
Wire Size AWG Electrical Current - Maximum per	Contact	N/A	
Grounding to Panel Shield Type Shielded Voltage - Maximum		Screw Hole EMI Gasket Yes 30V AC	

Solder Process Data Lead-free Process Capability Process Temperature max. C	Reflow Capable (SMT only) 260
Material Info Country of Origin	CN, IE
<b>Reference - Drawing Numbers</b> Application Specification Packaging Specification Product Specification	AS-91803-001 PK-91525-002, PK-91803-001 PS-91525-001

\* InfiniBand is a trademark of the InfiniBand Trade Association

Sales Drawing

This document was generated on 12/17/2010 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

SD-91804-003