
Resources

My Account

Customer Support

Home > Products > By Type > D Subminiature > Product Feature Selector > Product Details

5787083 - 7 Product Details



5787083

Active

.050 Series Board Mount Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance

Product Highlights:

- Connector
- Receptacle
- Number of Positions = 68
- Shielded
- With Mating Connector Lock

View all Features | Find Similar

Live Product Chat US

Quick Links

Check Pricing & Availability Search for Tooling Product Feature Selector Contact Us About This Product

Documentation & Additional Information

Product Drawings:

? RECEPTACLE ASSEMBLY, SHIELDED, RIGHT ANGLE, (PDF, English)

Catalog Pages/Data Sheets:

? None Available

Product Specifications:

Connector, AMPLIMITE, Shielded, .050 Series (PDF, English)

Application Specifications:

AMPLIMITE .050 Series Insulation Displacement and Pr... English)

Instruction Sheets:

? None Available

CAD Files: (CAD Format & Compression Information

- 2 2D Drawing (DXF, Version O)
- ? 3D Model (IGES, Version O)
- ? 3D Model (STEP, Version O)

Additional Information:

? Product Line Information

Additional Product Images:

Panel Cutout

Related Products:

? Tooling

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Product Type = Connector
- ? Gender = Receptacle
- ? Number of Positions = 68
- ? Shielded = Yes
- ? Mating Connector Lock = With
- ? Mount Angle = Right Angle
- ? PCB Polarization = Without
- ? PCB Retention Feature = Yes
- ? Rails = Without
- ? Shell Type = Full Metal
- ? Product Series = Series III
- ? Mating Connector Lock Type = Latch Blocks
- ? Shell Material = Steel
- ? Bracket Material = Zinc
- ? PCB Thickness (mm [in]) = 2.36 [0.093]

Mechanical Attachment:

- Pracket Plating = Nickel over Copper
- ? Boardlock Material = Copper Alloy
- ? Boardlock Plating = Tin over Nickel

Termination Related Features:

Termination (Solder) Post Length (mm [in]) 3.05 [0.120]

Body Related Features:

- PCB Retention Method = Boardlock(s)
- Post Plating = Tin over Nickel
- ? Shell Plating = Bright Tin

Contact Related Features:

- Contact Mating Area Plating Material (30), Gold Flash over Palladium Nickel
- Contact Material = Phosphor Bronze

Housing Related Features:

- ? Housing Material = Thermoplastic
- ? Housing Flammability Rating = UL 94V
- ? Housing Color = Black

Industry Standards:

? RoHS/ELV Compliance = RoHS compliant, ELV

-0

- <u>Lead Free Solder Processes</u> = Reflow solder capable to 245°C, Reflow solder capable to
- RoHS/ELV Compliance History = Always was RoHS compliant

Other:

? Brand = AMP

Provide Website Feedback | Contact Customer Support