

Products Documentation Resources My Account Customer Support

Home > Products > Socket/Card Products > Product Feature Selector > Product Details

390262-1 Product Details

Have a Question?

Chat with a Product Information Specialist

Quick Links

Check Pricing & Availability Search for Tooling

Contact Us About This Product

Product Feature Selector





DIP Sockets

Not EU RoHS or ELV Compliant (Find RoHS Compliant Alternates)

Product Highlights:

- · Socket Style = Standard
- Through Hole Contact Termination Type
- 2.54 mm Centerline
- Row-to-Row Spacing = 15.24 mm
- 24 Positions

View all Features

TE Internal Number: 390262-1 Superseded Superseded

Search for Replacement Parts











Documentation & Additional Information

Product Drawings:

DIP SOCKET, .600 CENTER LINE LADDER STYLE (PDF, English)

Catalog Pages/Data Sheets:

Product Specifications:

Application Specifications:

Instruction Sheets:

CAD Files:

None Available

Additional Information:

Related Products:

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Socket Style = Standard
- Profile = Standard
- Frame Style = Ladder
- Leg Style = Straight
- PCB Mount Angle = Horizontal

Electrical Characteristics:

- Insulation Resistance (MΩ) = 10,000
- Contact Resistance (mΩ) = 30

Termination Related Features:

- Termination Post Length (mm [in]) = 3.00 [0.118]
- Solder Tail Contact Plating = Tin-Lead

Body Related Features:

- Centerline (mm [in]) = 2.54 [0.100]
- Row-to-Row Spacing (mm [in]) = 15.24 [0.600]
- Number of Positions = 24
- Mount Style = Vertical

Contact Related Features:

List all Documents

- Contact Termination Type = Through Hole
- Contact Base Material = Phosphor Bronze
- · Contact Plating, Mating Area, Material = Tin-Lead
- Contact Style = Stamped + Formed
- Mating Contact Type = Dual Leaf

Configuration Related Features:

• Height Above PC Board (mm [in]) = 5.10 [0.200]

Industry Standards:

- RoHS/ELV Compliance = Not ELV/RoHS compliant
- <u>Lead Free Solder Processes</u> = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Conditions for Usage:
• Temperature Range (°C) = -40 - +105

Packaging Related Features:

Packaging Method = Tube

Other:

Brand = AMP

🟮 BOOKMARK 📑 😭 🧦 ...)

Corporate Information **Ouick Links**

Who We Are Check Distributor Inventory Investors Cross Reference News Room Find Documents & Drawings Supplier Portal

Product Compliance Support Center Site Map

Customer Support Email or Chat with Us Find a Phone Number Search Knowledge Base Manage Your Account

Sign up for our eNewsletter

Enter your email address



Follow us on:

Provide Website Feedback

© 2010 Tyco Electronics All Rights Reserved | Privacy Policy

Careers