


**Product Details for 6318916 - 1**



**6318916 - 1**

[Active](#)

**Memory Sockets**

[RoHS Compliant \(Statement of Compliance\)](#)

**Product Highlights:**

- ? Gold Flash over Nickel Contact Mating Area Plating
- ? Fax Modem Socket
- ? Number of Positions = 124
- ? .80 mm Centerline
- ? Stack Height = 5.20 mm

[View all Features](#)

**Quick Links**

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

**Documentation & Additional Information**

**Product Drawings:**

- ? [SEMI-HARD TRAY ASSY 0.8mm PITCH FAX MODEM SOCKET 124...](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- ? None Available

**Product Specifications:**

- ? [AMP FAXMODEM CONNECTOR LEAD FREE VERSION PRODUCT SPEC](#) (PDF, English)

**Application Specifications:**

- ? None Available

**Instruction Sheets:**

- ? [0.8mm Pitch Faxmodem Socket](#) (PDF, English)

**CAD Files:**

- ? None Available

**Additional Information:**

- ? [Product Line Information](#)

**Related Products:**

- ? [Tooling](#)

[List all Documents](#)

**Product Features** (Please use the Product Drawing for all design activity)

**Product Type Features:**

- ? Product Type = Fax Modem Socket
- ? [Number of Positions](#) = 124
- ? [Module Orientation](#) = Right Angle

**Body Related Features:**

- ? [Centerline \(mm \[in\]\)](#) = 0.80 [0.031]
- ? [Number of Rows](#) = Dual
- ? [Ejector Location](#) = None
- ? [Number of Keys](#) = 1
- ? Latch Material = Stainless Steel
- ? Latch Plating = Tin

**Contact Related Features:**

- ? Contact Mating Area Plating = Gold Flash over Nickel
- ? [Contact Mount](#) = Surface Mount
- ? Contact Material = Phosphor Bronze
- ? Contact Termination Area Plating = Gold Flash

**Housing Related Features:**

- ? Housing Material = High Temperature Thermoplastic
- ? Housing Flammability Rating = UL 94V -0
- ? Housing Color = Black

**Configuration Related Features:**

- ? Stack Height (mm [in]) = 5.20 [0.205]
- ? [Insertion Style](#) = Cam -In

**Industry Standards:**

- ? [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- ? [Lead Free Solder Processes](#) = Reflow solder capable to 245°C
- ? RoHS/ELV Compliance History = Always was RoHS compliant

**Packaging Related Features:**

- ? Packaging Method = Tray
- ? Packaging Quantity = 20

**Other:**

- ? Brand = AMP