

0548	8975	3016	9548
<p><b>0548-0-15-XX-21-XX-10-0</b> Solder mount in 0,91 min. mounting hole</p>	<p><b>8975-0-15-XX-21-XX-10-0</b> Solder mount in 0,91 min. mounting hole</p>	<p><b>3016-0-15-XX-21-XX-10-0</b> Solder mount in 0,91 min. mounting hole</p>	<p><b>9548-0-15-XX-21-XX-10-0</b> Solder mount in 0,91 min. mounting hole</p>

8637	1407	0553/8553															
		<table border="1" style="margin-top: 10px;"> <thead> <tr> <th>Basic Part Number</th> <th>Length L</th> <th>Depth N</th> </tr> </thead> <tbody> <tr> <td>0553-1</td> <td>3,56</td> <td>3,15</td> </tr> <tr> <td>0553-2</td> <td>4,32</td> <td>3,91</td> </tr> <tr> <td>0553-3</td> <td>7,16</td> <td>6,76</td> </tr> <tr> <td>8553-0</td> <td>6,22</td> <td>5,82</td> </tr> </tbody> </table>	Basic Part Number	Length L	Depth N	0553-1	3,56	3,15	0553-2	4,32	3,91	0553-3	7,16	6,76	8553-0	6,22	5,82
Basic Part Number	Length L	Depth N															
0553-1	3,56	3,15															
0553-2	4,32	3,91															
0553-3	7,16	6,76															
8553-0	6,22	5,82															
<p><b>8637-0-15-XX-21-XX-10-0</b> Solder mount in 0,94 min. mounting hole</p>	<p><b>1407-0-15-XX-11-XX-10-0</b> Solder mount in 1,02 min. mounting hole</p>	<p><b>X553-X-15-XX-X1-XX-10-0</b> Hex press-fit in 1,04 plated thru hole</p>															

0566	0442	0554						
<p><b>0566-X-15-XX-21-XX-10-0</b> Solder mount in 1,0 min. mounting hole</p> <table border="1" style="margin-top: 10px;"> <thead> <tr> <th>Basic Part Number</th> <th>Length L</th> </tr> </thead> <tbody> <tr> <td>0566-1</td> <td>2,11</td> </tr> <tr> <td>0566-2</td> <td>3,51</td> </tr> </tbody> </table>	Basic Part Number	Length L	0566-1	2,11	0566-2	3,51	<p><b>0442-0-15-XX-11-XX-10-0</b> Solder mount in 1,02 min. mounting hole</p>	<p><b>0554-0-15-XX-21-XX-10-0</b> Solder mount in 1,02 min. mounting hole</p>
Basic Part Number	Length L							
0566-1	2,11							
0566-2	3,51							

<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY</b></p> <p><b>TOLERANCES ON:</b> LENGTHS: ± 0,13 DIAMETERS: ± 0,05 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 15 - XX - XX - XX - 10 - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b></p> <p><b>01</b> 5,08µm TIN/LEAD OVER NICKEL</p> <p><b>80</b> 5,08µm TIN OVER NICKEL ◊</p> <p><b>15</b> 0,25µm GOLD OVER NICKEL ◊</p> <p><b>SPECIFY CONTACT FINISH:</b></p> <p><b>02</b> 2,54µm TIN/LEAD OVER NICKEL</p> <p><b>84</b> 2,54µm TIN OVER NICKEL ◊</p> <p><b>27</b> 0,76µm GOLD OVER NICKEL ◊</p> <p><b>SELECT CONTACT</b></p> <p><b>#11 or #21 CONTACT (DATA ON PAGE 206)</b></p>
--	---

