

COMPANY:	CONTACT:	
TELEPHONE:	FAX:	

QUANTITY:

CUSTOM SOCKETS CPAS SERIES

may apply. Call Samtec.

Customize your PGA sockets and optimize your costs

Samtec offers the ultimate in PGA socket and adaptor flexibility. If you don't find the pin out you need among our most popular patterns, fax it to us and we will check it against the thousands of standards we stock.

Even if we don't stock it, customs are a specialty at Samtec. Choose from the many insulator types, lead socket and terminal styles, platings and grid sizes to build your own socket or adaptor. Fill in the part number and indicate your pattern and we'll quote price and delivery.

SPECIFICATIONS

For complete specifications see www.samtec.com?CPAS

Insulator Material:
Black G.F. Polyester
Contact: BeCu
Shell: Brass except MEMO EITISM
Style K. Phospher Bronze Operating Temp Range: -55°C to +105°C with Tin -55°C to +125°C with Gold Plating:

Au over 50µ"(1,27µm) Ni or Sn over 100µ" (2,58µm) Cu or 50µ" (1,27µm) Ni **Current Rating:**

Contact Resistance:

10mΩ max Lead Size Range: .015" (0,38mm) to .022" (0,56mm) DIA except Style ZL = .015" (0,38mm) to .020" (0,51mm) DIA

Insertion Force: (Single contact only) Style ZU

Withdrawal Force: (Single contact only) Style ZU = 1.5oz (0,42N) max, all others = 2.0 oz (0,56N) avg, 0.35 oz (0,97N) min, except Styles J & K = 2.50 oz (0,69N) avg, 1.5 oz

(0,42N) min Lead-Free Solderable: Wave, only RoHS Compliant:

CPAS	PIN	LEAD STYLE	PLATING OPTION	GRID SIZE	PIN OUT CODE	-	OPTION
Note: These Series are non-standard, non-retur	-XXX = Total Number Of Filled Positions	Select socket styles from MXAS series.	Select socket plating from MXAS series.	08 thru —1 = CPAS Series		I	-2 =.360 (9,14μm) (-ZW only) -3 =.260 (6,60μm) (-ZW only) -L = Locking socket (-ZS only)

MARK PIN OUT ON GRID

(Leave part number blank, Samtec will determine.)

	_	В	С				G											Т	U	٧	W	Х	Υ	<u>z</u>
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
7	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
8	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
9	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
10	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
11	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
12	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
13	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
14	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
15	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
16	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
17	0	0	0	0	0	0	0	0	0	-	-	-	_	-	_	0	0	0	0	0	0	0	0	이
18	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
19	0	0	0	0	0	0	0	0	0	-	-	-	-	-	0		0	0	0	0	0	0	0	이
20	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
21	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
22	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
23	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	이
24	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	<u>o</u>

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM