



# ADAPTOR PLUGS APA SERIES

Mates with:  
ICO, ICA, CIC

## FEATURES

- Side & end stackable
- Great for auto insertion
- Open body design

## SPECIFICATIONS

For complete specifications see [www.samtec.com?APA](http://www.samtec.com?APA)

**Insulator Material:**  
Black Glass Filled Polyester except -328 is LCP



**Flammability Rating:**  
UL 94V-0

**Insulation Resistance:**  
5000 MΩ min

**Operating Temp Range:**  
-55°C to +105°C with Tin;  
-55°C to +125°C with Gold.

**Withstanding Voltage:**  
1000 VRMS

**Terminal Material:**  
Brass except styles -M, -N,  
-P and -Q are Phosphor  
Bronze or Brass

**Plating:**  
Au over 50μ" (1,27mm) Ni or  
Sn over 100μ" (2,54mm) Cu  
or 50μ" (1,27mm) Ni

**Current Rating:**  
1 A  
**Terminal Retention in Body:**  
5 lbs (22,25N) against barb

APA	ROW SPACING & NO. OF PINS	PLATING OPTION	LEAD STYLE																														
Specify from chart below																																	
	<table border="1"> <thead> <tr> <th>Row Space</th> <th>No. of Pins</th> </tr> </thead> <tbody> <tr><td>-308</td><td>08</td></tr> <tr><td>-314</td><td>14</td></tr> <tr><td>-316</td><td>16</td></tr> <tr><td>-318</td><td>18</td></tr> <tr><td>-320</td><td>20</td></tr> <tr><td>-322*</td><td>22</td></tr> <tr><td>-324</td><td>24</td></tr> <tr><td>-328</td><td>28</td></tr> <tr><td>-422</td><td>22</td></tr> <tr><td>-624</td><td>24</td></tr> <tr><td>-628</td><td>28</td></tr> <tr><td>-632</td><td>32</td></tr> <tr><td>-640</td><td>40</td></tr> <tr><td>-648</td><td>48</td></tr> </tbody> </table>	Row Space	No. of Pins	-308	08	-314	14	-316	16	-318	18	-320	20	-322*	22	-324	24	-328	28	-422	22	-624	24	-628	28	-632	32	-640	40	-648	48	<p><b>-G</b> = 20μ" (0,58μm) Gold</p> <p><b>-T</b> = Tin</p>	
	Row Space	No. of Pins																															
	-308	08																															
	-314	14																															
	-316	16																															
	-318	18																															
	-320	20																															
	-322*	22																															
	-324	24																															
	-328	28																															
	-422	22																															
	-624	24																															
-628	28																																
-632	32																																
-640	40																																
-648	48																																
* -322 has no cross bar on one end.																																	

### -A or -A1 = Round Pin

STYLE	X DIA
-A	(0,64)
-A1	(0,46)

Style A Component No. = T-1R0-  
Style A1 Component No. = T-1R5-

### -C = Slotted Head

Component No. = T-1R2-

### -D = Wire-Wrap

Component No. = T-1S4-1-1

### -F = Flat-head W.W.

Component No. = T-1S2-

### -J = Solder Shell

Component No. = S-1P1-

### -K = Test Point

Component No. = T-1R15-

### -M, -N or -P = Interconnect Post

Not available with -328 body.

STYLE	Y
-M	(1,52) .060
-N	(4,69) .185
-P	(11,05) .435

Component No. = T-1R14-

**Note:**  
Some sizes, styles and options are non-standard, non-returnable.

Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047  
 SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299  
 SAMTEC NORDIC/BALTIC • Tel: +46-84477280 • Fax: +46-87420413  
 SAMTEC ASIA PACIFIC • Tel: 65 6745-5955 • Fax: 65 6841-1502  
 SAMTEC HONG KONG • Tel: 852-2800-4850 • Fax: 852-2800-4842  
 SAMTEC JAPAN • Tel: 045-475-1385 • Fax: 045-475-1340  
 SAMTEC KOREA • Tel: 82-31-717-5685 • Fax: 82-31-717-5681  
 SAMTEC SILICON VALLEY • Tel: 408-395-5900 • Fax: 408-395-1520  
 SAMTEC FRANCE • Tel: 01 60 95 06 60 • Fax: 01 60 95 06 61  
 SAMTEC CHINA • Tel: 86-21-61103766 • Fax: 86-21-5423 4575  
 SAMTEC SOUTH AFRICA • Tel: 27 11 454 4317 • Fax: 27 86 6714432  
 SAMTEC UK • Tel: 01236 739292 • Fax: 01236 727113  
 SAMTEC ITALY • Tel: 39 039 6890337 • Fax: 39 039 6890315  
 SAMTEC INDIA • Tel: +91-80-3272 1612 • Fax: +91-80-4152 8187  
 SAMTEC TAIWAN • Tel: 886-2-2735-6109 • Fax: 886-2-2735-5036  
 SAMTEC ANZ • Tel: 613 9512 7747 • Fax: 613 9512 7745