


## 132-0202-0002 Product Details

Live Product Chat



**132-0202-0002**  
(5-1532005-5)

TE Part Number: 5-1532005-5

Active

Add to Part List

### SMB RF Connectors

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- Connector
- Plug
- Miniature
- Terminate To Coaxial Cable
- Coupler Style = Threaded

[View all Features](#) | [Find Similar Products](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

### Documentation & Additional Information

#### Product Drawings:

- [S-70 GLD CRIMP RT ANGLE PLUG](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- [Golden Crimp and Crimp Silver Right-Angle Connectors](#) (PDF, English)

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- [Product Type](#) = Connector
- [Gender](#) = Plug
- Connector Series = Miniature
- [Body Style](#) = Right Angle
- [Grade](#) = Commercial
- Safety Wire Holes = Without
- Thread Size = 5.49 [.216]-32
- Body Material = Brass
- Coupling Nut Style = Knurled
- Dielectric Material = TEFLON

#### Mechanical Attachment:

- [Panel Attachment](#) = Without

#### Electrical Characteristics:

- [Connector Impedance \(Ω\)](#) = 70
- Environmental Seal = Without
- Solderless = Yes

#### Termination Related Features:

- [Coaxial Cable Termination Type](#) = Crimp

#### Body Related Features:

- Coupler Style = Threaded
- [Pin Protection](#) = Without
- Solder Lug = Without
- [Body Plating](#) = Gold per MIL-G-45204, Type II, Grade C, Class 1
- Cable Jacket Diameter (mm [in]) = 2.79 [0.110]

#### Contact Related Features:

- [Center Contact Plating](#) = Gold per MIL-G-45204, Type II, Grade C, Class 1
- Contacts = With

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Conditions for Usage:

- [Terminate To](#) = Coaxial Cable

#### Other:

- Brand = Microdot