


## 6376727-1 Product Details

Live Product Chat



**6376727-1**

TE Part Number: 6376727-1

Active

Add to Part List

### Memory Sockets

Always EU RoHS/ELV Compliant (Statement of Compliance)

#### Product Highlights:

- Fax Modem Socket
- Gold Flash Contact Mating Area Plating Material
- Number of Positions = 124
- Row-to-Row Spacing = 6.20 mm
- .80 mm Centerline

[View all Features](#) | [Find Similar Products](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

### Documentation & Additional Information

#### Product Drawings:

- [SEMI-HARD TRAY ASSY 0.8mm PITCH FAX MODEM SOCKET 124...](#) (PDF, English)

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- [AMP FAXMODEM CONNECTOR LEAD FREE VERSION PRODUCT SPEC](#) (PDF, English)

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Product Type = Fax Modem Socket
- [Number of Positions](#) = 124
- [Module Orientation](#) = Right Angle
- PCB Retention Feature = Yes

#### Mechanical Attachment:

- Keying = Standard

#### Body Related Features:

- [Row-to-Row Spacing \(mm \[in\]\)](#) = 6.20 [0.244]
- [Centerline \(mm \[in\]\)](#) = 0.80 [0.031]
- [Number of Rows](#) = Dual
- Ejector Type = Locking
- [Ejector Location](#) = Both Ends
- Center Post = Without
- [Number of Keys](#) = 1
- PCB Retention Method = Hold Down Post

#### Contact Related Features:

- Contact Mating Area Plating Material = Gold Flash
- [Contact Mount](#) = Surface Mount
- Contact Material = Phosphor Bronze
- [Retention Post\(s\) Location](#) = Both Ends

#### Housing Related Features:

- Housing Material = High Temperature Thermoplastic
- Housing Color = Black
- Housing Flammability Rating = UL 94V-0

#### Configuration Related Features:

- [Stack Height \(mm \[in\]\)](#) = 4.00 [0.157]
- [Insertion Style](#) = Cam-In
- [Center Key \(mm \[in\]\)](#) = Offset Left

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245°C
- RoHS/ELV Compliance History = Always was RoHS compliant

#### Operation/Application:

- Application Type = Mini-PCI

#### Packaging Related Features:

- Packaging Method = Tray
- Packaging Quantity = 20 Pieces/Tray

#### Other:

- Brand = AMP