


ICF-624-S-O



PLCC-068-F-A

(2,54mm) .100"

ICF, PLCC SERIES

# SMT DIP & CHIP CARRIER SOCKETS

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?ICF](http://www.samtec.com?ICF)

**Insulator Material:** Black LCP



**Contact Material:** BeCu

**Plating:** Au or Sn over 50µ" (1,27µm) Ni

**Current Rating:** 1A

**Operating Temp Range:** -55°C to +125°C

**Contact Resistance:** 10 mΩ Max

**Insertion Depth:** (2,54mm) .100" to (3,81mm) .150"

**Insertion Force/Contact:** 5oz (1,39N) average

**Withdrawal Force/Contact:** 4oz (1,11N) average

**RoHS Compliant:** Yes

**Processing:**

**Lead-Free Solderable:** Yes

**SMT Lead Coplanarity:** .006" (0,15mm) max



ICF

ROW SPACING & NO. OF CONTACTS

PLATING OPTION

TAIL OPTION

OTHER OPTION

**TIGER EYE™ CONTACT**

Specify from chart below

"-XXX"	Row Space	No. of Contacts
-308	.300 (7,62)	08
-314		14
-316		16
-318		18
-320		20
-322	.600 (15,24)	22
-324		24
-328		28
-624		24
-628		28
-632	.600 (15,24)	32
-640		40
-648		48

-S =30µ" (0,76µm) Gold on contact, Matte Tin on tail

-T = Matte Tin

-I =Tails In

-O =Tails Out

-TR =Tape & Reel Packaging

**Note:** Some sizes, styles and options are non-standard, non-returnable.

## SPECIFICATIONS

For complete specifications and recommended PCB layouts see [www.samtec.com?PLCC](http://www.samtec.com?PLCC)

**Insulator Material:** Black Liquid Crystal Polymer



**Contact Material:** BeCu

**Plating:** Sn or Au over 50µ" (1,27µm) Ni

**Current Rating:** 1A

**Operating Temp Range:** -55°C to +105°C

**Contact Resistance:** 10mΩ max

**RoHS Compliant:** Yes

**Processing:**

**Lead-Free Solderable:** Yes

**Lead Coplanarity:** Less than 52 leads= .006" (0,15mm) max; 52 leads and more= .008" (0,20 mm) max

PLCC

NO. OF CONTACTS

PLATING OPTION

ALIGNMENT PIN OPTION

PACKAGE OPTION

**-020, -028, -032, -044, -052, -068, -084**

NO. OF PINS	A	B	C	D
-020	.600 (15,24)	.600 (15,24)	.370 (9,40)	.370 (9,40)
-028	.700 (17,78)	.700 (17,78)	.470 (11,94)	.470 (11,94)
-032	.800 (20,32)	.800 (20,32)	.570 (14,48)	.570 (14,48)
-044	.900 (22,86)	.900 (22,86)	.670 (17,02)	.670 (17,02)
-052	1.000 (25,40)	1.000 (25,40)	.770 (19,56)	.770 (19,56)
-068	1.200 (30,48)	1.200 (30,48)	.970 (24,64)	.970 (24,64)
-084	1.400 (35,56)	1.400 (35,56)	1.170 (29,72)	1.170 (29,72)

-F =Gold flash on contact, Matte Tin on tail

-T = Matte Tin


-N =No Alignment Pins

-A =Alignment Pins

-TR =Tape and Reel

Leave package option blank for packaging in a tube.

**Note:** Some sizes, styles and options are non-standard, non-returnable.



Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)