

4011	1801	1001	0156
<p>4011-0-15-XX-30-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>1801-0-15-XX-30-XX-04-0 Press-fit in 1,45 mounting hole Shell is Ph. Br. Alloy 544 (B2)</p>	<p>1001-0-15-XX-3X-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>0156-0-18-XX-30-XX-04-0 Self-retention socket pin 0,97 -1,09 hole prior to soldering</p>

0255	1109	3013	0134
<p>0255-0-15-XX-30-XX-04-0 Solder mount in 0,56 min. mounting hole</p>	<p>1109-0-15-XX-30-XX-04-0 Hex press-fit in 1,45 plated thru hole</p>	<p>3013-0-15-XX-32-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>0134-0-15-XX-3X-XX-04-0 Press-fit in 1,45 mounting hole</p>

0132/0135	0133/0147												
<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0132-0</td> <td>6,93</td> </tr> <tr> <td>0135-0</td> <td>4,65</td> </tr> </tbody> </table>	Basic Part Number	Length A	0132-0	6,93	0135-0	4,65	<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Length A</th> </tr> </thead> <tbody> <tr> <td>0133-0</td> <td>9,7</td> </tr> <tr> <td>0147-0</td> <td>14,3</td> </tr> </tbody> </table>	Basic Part Number	Length A	0133-0	9,7	0147-0	14,3
Basic Part Number	Length A												
0132-0	6,93												
0135-0	4,65												
Basic Part Number	Length A												
0133-0	9,7												
0147-0	14,3												
<p>013X-0-15-XX-30-XX-04-0 Press-fit in 1,45 mounting hole</p>	<p>01XX-0-15-XX-30-XX-04-0 Press-fit in 1,5 mounting hole</p>												

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY</p> <p>TOLERANCES ON: LENGTHS: ± 0,13 DIAMETERS: ± 0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 1X - XX - 3X - XX - 04 - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL 80 5,08µm TIN OVER NICKEL ◊ 15 0,25µm GOLD OVER NICKEL ◊</p> <p>SPECIFY CONTACT FINISH: →</p> <p>02 2,54µm TIN/LEAD OVER NICKEL 84 2,54µm TIN OVER NICKEL ◊ 27 0,76µm GOLD OVER NICKEL ◊</p> <p>SELECT CONTACT #32 or #32 CONTACT (DATA ON PAGE 208)</p>

Downloaded from Elcodis.com electronic components distributor