



DATE WED, 09-JUL-2008 07:43:41

PRINT OUT

CLOSE WINDOW

COAXIAL PANEL CONNECTORS ONLINE DATA BASE

[New selection](#)

- [\[Mechanical\]](#)
- [\[Electrical\]](#)
- [\[Environmental\]](#)
- [\[Material\]](#)

Item details

Item description

23_N-50-0-31/133_NE

Connector Description

Straight panel receptacle jack, flange mount

Series / Pattern
Highlights• N – Type / [Pattern 23](#)

Item number

22642836

Catalogue drawing

[23_N-50-0-31](#)

Related documents

[3D Model](#) - STEP format AP203/214

2002/95/EC (RoHS)

compliant

Interface Standards

IEC 61169-16; MIL-STD-348A/304; CECC 22210

Mechanical data[Jump to \[Top\]](#)

Flange Dimension

Type square flange

12.7 x 12.7 mm

Tab Style

solder end

Terminal Dimension D1

1.26 mm

Terminal Dimension L1

4.5 mm

Electrical data[Jump to \[Top\]](#)

Impedance

50 Ω

Interface Freq max

≤11 GHz

Environmental and general data[Jump to \[Top\]](#)

Operating Temp min

-65 °C

Operating Temp max

165 °C

Weight

0.0155 kg

Number of Matings

500

Material data[Jump to \[Top\]](#)

2002/95/EC (RoHS)

compliant

Piece part**Base material****Plating**

Center contact

Copper Beryllium Alloy

Gold Plating (Nickel underplated)

Outer contact

Brass

SUCOPLATE (R) Plating

Insulator

PFA / PTFE

Body

Brass

SUCOPLATE (R) Plating

[privacy policy](#) | [disclaimer](#) © 2007 HUBER+SUHNER